



### Main

Range of product	Concept
Range	Concept
Product or component type	Switch
Device presentation	Mechanism
Device application	Switch
Colour tint	White
Sale per indivisible quantity	1
Load type	Inductive 1 W

### Complementary

Device mounting	Flush
Switch function	1-way
Number of modules	1.5 modules 34.75 x 46 mm
Number of rocker	1
Actuator	Rocker
Fixing mode	Clip-in
Surface finish	Glossy
Surface treatment	Untreated
Rated current	16 AX 250 V AC 50/60 Hz
Electrical durability	20000 cycles IEC 60669
Connections - terminals	Screwless terminals 2
Clamping connection capacity	<= 4 mm <sup>2</sup> rigid
Wire stripping length	12 mm
Material	PC (polycarbonate) base PC (polycarbonate) dolly PC (polycarbonate) base cover Copper load side Steel screwless terminal PC (polycarbonate) actuator

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Silver alloy rivet  
PBT (polybutylene terephthalate) GF30 release key  
Steel springs

Height	46 mm
Width	34.75 mm
Depth	33 mm

## Environment

Ambient air temperature for operation	-5...45 °C
Relative humidity	0...95 %
Standards	IEC 60669
IP degree of protection	IP20

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1715 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations