



## Main

Range of product	Concept
Range	Concept
Product or component type	Socket-outlet
Device presentation	Mechanism
Outlet poles configuration	2P + E with shutter
Outlet standard description	With earthing contact
Outlet standard	Universal
Colour tint	Red
Type of packing	Flow-pack
Sale per indivisible quantity	1

## Complementary

Number of power socket outlets	2
Device mounting	Flush
Ground lug position	Straight 0° position
Number of modules	3 modules
Fixing mode	Clip-in
Pin number	3
Surface finish	Glossy
Rated current	16 A 250 V AC 50...60 Hz
Electrical durability	5000 cycles
Connections - terminals	Push-in 3
Number of cables	3
Clamping connection capacity	1.5...4 mm <sup>2</sup> rigid 1.5...4 mm <sup>2</sup>
Wire stripping length	12 mm
Material	Steel spring PC (polycarbonate) cover

	PC (polycarbonate) base Brass contact Nylon + GF shutter Steel terminals
Height	38 mm
Width	46 mm
Depth	70 mm
Embedding depth	37 mm

## Environment

Ambient air temperature for storage	-5...50 °C
Dielectric strength	2000 V
Ambient air temperature for operation	-5...35 °C
Standards	IEC 60884-1
IP degree of protection	IP21
Environmental characteristic	Liquid soap Ammonia Oil Acetone Bleach Hydrogen peroxide (H2O2) UV resistant Alcohol Window-cleaning fluid Petrol
Environmental health and issues	Halogen free

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1715 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations