



## Main

|                               |                       |
|-------------------------------|-----------------------|
| Range of product              | Concept               |
| Range                         | Concept               |
| Product or component type     | Socket-outlet         |
| Device presentation           | Mechanism             |
| Outlet poles configuration    | 2P + E with shutter   |
| Outlet standard description   | With earthing contact |
| Outlet standard               | Universal             |
| Colour tint                   | White                 |
| Type of packing               | Flow-pack             |
| Sale per indivisible quantity | 1                     |

## Complementary

|                                |  |
|--------------------------------|--|
| Number of power socket outlets | 1  |
| Device mounting                | Flush  |
| Ground lug position            | Straight 0° position                                     |
| Number of modules              | 1.5 modules  |
| Fixing mode                    | Clip-in  |
| Pin number                     | 3  |
| Surface finish                 | Glossy   |
| Rated current                  | 16 A 250 V AC 50...60 Hz                                 |
| Electrical durability          | 5000 cycles  |
| Connections - terminals        | Push-in 3  |
| Number of cables               | 3  |
| Clamping connection capacity   | 1.5...4 mm <sup>2</sup> rigid<br>1.5...4 mm <sup>2</sup> |
| Wire stripping length          | 12 mm  |
| Material                       | Steel spring<br>PC (polycarbonate) cover                 |

|                 |   |
|-----------------|---|
|                 | PC (polycarbonate) base<br>Brass contact<br>Nylon + GF shutter<br>Steel terminals |
| Height          | 30.6 mm   |
| Width           | 46 mm   |
| Depth           | 46.7 mm   |
| Embedding depth | 29.6 mm   |

## Environment

|                                       |  |
|---------------------------------------|--|
| Ambient air temperature for storage   | -5...50 °C   |
| Dielectric strength                   | 2000 V   |
| Ambient air temperature for operation | -5...35 °C   |
| Standards                             | IEC 60884-1  |
| IP degree of protection               | IP21   |
| Environmental characteristic          | Ammonia<br>UV resistant<br>Bleach<br>Alcohol<br>Liquid soap<br>Oil<br>Acetone<br>Petrol<br>Hydrogen peroxide (H2O2)<br>Window-cleaning fluid |
| Environmental health and issues       | Halogen free   |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1715 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |