

Main

Range of product	TeSys E
Product or component type	Auxiliary contact block
Product compatibility	TeSys E contactor
Mounting location	Front side
Pole contact composition	2 NC

Complementary

[Ui] rated insulation voltage	690 V for control circuit conforming to IEC 60947-5-1
Connections - terminals	Control circuit: screw clamp terminals - 2 solid or flexible cable(s) 2.5 mm ² Ø6 mm without cable end Control circuit: screw clamp terminals - 2 solid or flexible cable(s) 2.5 mm ² Ø6 mm with cable end Control circuit: screw clamp terminals - 1 solid or flexible cable(s) 1 mm ² Ø6 mm without cable end Control circuit: screw clamp terminals - 1 solid or flexible cable(s) 1 mm ² Ø6 mm with cable end
[Ith] conventional free air thermal current	8 A at ≤ 60 °C
Irms rated making capacity	140 A conforming to IEC 60947-5-1
Permissible short-time rating	140 A - 100 ms 120 A - 500 ms 100 A - 1 s
Protection type	GG fuse ≤ 10 A conforming to VDE 0660 GG fuse ≤ 10 A conforming to IEC 60947-5-1
Mechanical durability	10000000 cycles
Non-overlap time	1.5 ms on de-energisation (no overlap between NC and NO contact) 1.5 ms on energisation (no overlap between NC and NO contact)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Rated operational power in VA	80 VA at 440 V - AC-15 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 70 VA at 400 V - AC-15 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 40 VA at 230 V - AC-15 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 20 VA at 115 V - AC-15 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 8 VA at 48 V - AC-15 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 4 VA at 24 V - AC-15 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 300 VA at 440 V - AC-15 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 280 VA at 400 V - AC-15 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 160 VA at 230 V - AC-15 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 80 VA at 115 V - AC-15 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 32 VA at 48 V - AC-15 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 16 VA at 24 V - AC-15 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 1050 VA at 440 V - AC-15 - 1000000 cycles for control circuit conforming to IEC 60947-5-1 960 VA at 400 V - AC-15 - 1000000 cycles for control circuit conforming to IEC 60947-5-1 560 VA at 230 V - AC-15 - 1000000 cycles for control circuit conforming to IEC 60947-5-1 280 VA at 115 V - AC-15 - 1000000 cycles for control circuit conforming to IEC 60947-5-1 120 VA at 48 V - AC-15 - 1000000 cycles for control circuit conforming to IEC 60947-5-1 60 VA at 24 V - AC-15 - 1000000 cycles for control circuit conforming to IEC 60947-5-1 80 VA at 440 V - AC-14 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 70 VA at 400 V - AC-14 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 40 VA at 230 V - AC-14 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 20 VA at 115 V - AC-14 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 8 VA at 48 V - AC-14 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 4 VA at 24 V - AC-14 - 10000000 cycles for control circuit conforming to IEC 60947-5-1 300 VA at 440 V - AC-14 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 280 VA at 400 V - AC-14 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 160 VA at 230 V - AC-14 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 80 VA at 115 V - AC-14 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 32 VA at 48 V - AC-14 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 16 VA at 24 V - AC-14 - 3000000 cycles for control circuit conforming to IEC 60947-5-1 1050 VA at 440 V - AC-14 - 1000000 cycles for control circuit conforming to IEC 60947-5-1 960 VA at 400 V - AC-14 - 1000000 cycles for control circuit conforming to IEC 60947-5-1 560 VA at 230 V - AC-14 - 1000000 cycles for control circuit conforming to IEC 60947-5-1 280 VA at 115 V - AC-14 - 1000000 cycles for control circuit conforming to IEC 60947-5-1 120 VA at 48 V - AC-14 - 1000000 cycles for control circuit conforming to IEC 60947-5-1 60 VA at 24 V - AC-14 - 1000000 cycles for control circuit conforming to IEC 60947-5-1
Terminals description ISO n°1	(51-52)NC (61-62)NC
Product weight	0.035 kg

Environment

Standards	IEC 60947-5-1
Product certifications	GOST
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

Contractual warranty

Period	18 months
--------	-----------