

METSEPM5330

PM5330 powermeter w modbus - upto 31st H -
256K 2DI/2DO 35alarms - flush mount



Main

Range	PowerLogic
Product name	PowerLogic PM5000
Device short name	PM5330
Product or component type	Power meter
Market segment	Datacenter (Energy Cost management) for Cost allocation Main incomer in Industry (Energy Cost management) for Cost allocation Main incomer in Buildings / Medium building (Energy Cost management) for Billing Main incomer in Buildings / Medium building (Energy Cost management) for Billing Sub feeder in Buildings / Small building (Energy Cost management) for Cost allocation Main incomer in Buildings / Multi-site (Energy Cost management) for Billing Sub feeder in Healthcare (Energy Network management) Sub feeder in Industry (Energy Network management) Sub feeder in Buildings / Small building (Energy Network management) Sub feeder in Buildings / Medium building (Energy Network management) Sub feeder in Buildings / Medium building (Energy Network management) Main incomer in Buildings / Medium building (Energy Cost management) for Cost allocation Main incomer in Buildings / Small building (Energy Network management) Main incomer in Buildings / Small building (Energy Cost management) for Cost allocation Sub feeder in Datacenter (Energy Network management) Sub feeder in Buildings / Small building (Energy Cost management) for Billing Main incomer in Industry (Energy Cost management) for Cost allocation Sub feeder in Industry (Energy Cost management) for Billing Main incomer in Buildings / Multi-site (Energy Network management) Sub feeder in Buildings / Large building (Energy Cost management) for Cost allocation Main incomer in Buildings / Large building (Energy Cost management) for Billing Sub feeder in Industry (Energy Cost management) for Billing Sub feeder in Buildings / Multi-site (Energy Cost management) for Cost allocation Main incomer in Healthcare (Energy Cost management) for Billing Sub feeder in Datacenter (Energy Cost management) for Cost allocation Sub feeder in Buildings / Large building (Energy Cost management) for Billing Main incomer in Healthcare (Energy Cost management) for Cost allocation Sub feeder in Healthcare (Energy Cost management) for Billing Main incomer in Healthcare (Energy Cost management) for Cost allocation Main incomer in Buildings / Multi-site (Energy Cost management) for Cost allocation Sub feeder in Buildings / Multi-site (Energy Cost management) for Billing Main incomer in Buildings / Small building (Energy Cost management) for Billing Sub feeder in Buildings / Large building (Energy Network management) Sub feeder in Datacenter (Energy Cost management) for Billing Main incomer in

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Complementary

Power quality analysis	Up to the 31st harmonic
Device application	Multi-tariff Power monitoring
Type of measurement	Energy Active and reactive power Voltage Current Frequency Power factor
[Us] rated supply voltage	100...415 V AC (45...65 Hz) 125...250 V DC
Network frequency	60 Hz 50 Hz
[In] rated current	5 A 1 A
Poles description	3P 1P + N 3P + N
Power consumption in VA	10 VA at 415 V
Display type	Backlit LCD
Display resolution	128 x 128 pixels
Sampling rate	64 samples/cycle
Measurement current	10...9000 mA
Analogue input type	Current (impedance 0.3 mOhm) Voltage (impedance 5 MOhm)
Measurement voltage	35...690 V AC 45...65 Hz between phases 20...400 V AC 45...65 Hz between phase and neutral
Frequency measurement range	45...65 Hz
Number of inputs	2 digital
Measurement accuracy	+/- 0.5 % active energy +/- 2 % reactive energy +/- 0.5 % active power +/- 0.5 % apparent power +/- 0.05 % frequency +/- 0.005 % power factor +/- 0.5 % current +/- 0.5 % voltage
Accuracy class	Class 0.5S (active energy according to IEC 62053-22)
Number of outputs	2 digital 2 relay
Information displayed	Tariff 4
Communication port protocol	Modbus RTU and ASCII 2 wires, : 9.6, 19.2 and 38.4 kbauds, even/odd or none, insulation: 2500 V JBUS
Communication port support	RS485
Data recording	Alarm logs Maintenance logs Time stamping Min/Max of instantaneous values Data logs Event logs
Memory capacity	256 kB
Connections - terminals	Voltage circuit: 4 screw terminal block Control circuit: 2 screw terminal block Current transformer: 6 screw terminal block Input/Output circuit: 6 screw terminal block Relay output: 4 screw terminal block Ethernet network: RJ45 connector
Mounting mode	Flush-mounted

Mounting support	Framework
Standards	IEC 62053-24 IEC 62053-22 UL 61010-1 IEC 60529 EN 50470-1 EN 50470-3 IEC 61557-12
Product certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1
Width	96 mm
Depth	72 mm
Height	96 mm
Product weight	430 g

Environment

Electromagnetic compatibility	<ul style="list-style-type: none"> • conducted and radiated emissions class class B, conforming to EN 55022 • limits for harmonic current emissions class class A, conforming to IEC 61000-3-2 • electrostatic discharge class level 4, conforming to IEC 61000-4-2 • conducted RF disturbances class level 3, conforming to IEC 61000-4-6 • magnetic field at power frequency class level 4, conforming to IEC 61000-4-8
IP degree of protection	IP52 (front) conforming to IEC 60529 IP30 (body) conforming to IEC 60529
Relative humidity	5...95 % 50 °C
Pollution degree	2
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Operating altitude	2000 m

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1321 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available