



SIMATIC S7-1200 POWER MODULE PM1207 STABILIZED  
POWER SUPPLY INPUT: 120/230 V AC OUTPUT: 24 V DC/2.5 A

### Technical specifications

Product	S7-1200 PM1207
Power supply, type	24 V/2.5 A

### Input

Input	1-phase AC
Supply voltage 1 with AC Rated value	120 V
Supply voltage 2 with AC Rated value	230 V
• Note	Automatic range selection
Input voltage 1 with AC	85 ... 132 V
Input voltage 2 with AC	176 ... 264 V
Wide-range input	No
Overvoltage resistance	$2.3 \times V_{in}$ rated, 1.3 ms
Mains buffering at I <sub>out</sub> rated, min.	20 ms; at $V_{in} = 93/187$ V
Rated line frequency	50 ... 60 Hz
Rated line range	47 ... 63 Hz
Input current at rated input voltage 120 V Rated value	1.2 A
Input current at rated input voltage 230 V Rated value	0.67 A
Switch-on current limiting (+25 °C), max.	13 A
Duration of inrush current limiting at 25 °C maximum	3 ms
I <sup>2</sup> t, max.	0.5 A <sup>2</sup> ·s
Built-in incoming fuse	T 3,15 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: 16 A characteristic B or 10 A characteristic C

Output	
Output	Controlled, isolated DC voltage
Rated voltage Vout DC	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.2 %
Residual ripple peak-peak, max.	150 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	240 mV
Product function Output voltage adjustable	No
Output voltage setting	-
Status display	Green LED for 24 V OK
On/off behavior	No overshoot of Vout (soft start)
Startup delay, max.	6 s; 2 s at 230 V, 6 s at 120 V
Voltage rise, typ.	10 ms
Rated current value Iout rated	2.5 A
Current range	0 ... 2.5 A
Active power supplied typical	60 W
Short-term overload current on short-circuiting during the start-up typical	6 A
Duration of overloading capability for excess current on short-circuiting during the start-up	100 ms
Short-term overload current at short-circuit during operation typical	6 A
Duration of overloading capability for excess current at short-circuit during operation	100 ms
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2

Efficiency	
Efficiency at Vout rated, Iout rated, approx.	83 %
Power loss at Vout rated, Iout rated, approx.	12 W

Closed-loop control	
Dynamic mains compensation (Vin rated ±15 %), max.	0.3 %
Dynamic load smoothing (Iout: 50/100/50 %), Uout ± typ.	3 %
Load step setting time 50 to 100%, typ.	5 ms
Load step setting time 100 to 50%, typ.	5 ms
Setting time maximum	5 ms

Protection and monitoring	
Output overvoltage protection	< 33 V
Current limitation, typ.	2.65 A
Property of the output Short-circuit proof	Yes

Short-circuit protection	Constant current characteristic
Enduring short circuit current RMS value typical	2.7 A
Overload/short-circuit indicator	-

### Safety

Primary/secondary isolation	Yes
Galvanic isolation	Safety extra-low output voltage U <sub>out</sub> acc. to EN 60950-1 and EN 50178
Protection class	Class I
Leakage current maximum	3.5 mA
CE mark	Yes
UL/CSA approval	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus-Recognized (UL 60950-1, CSA C22.2 No. 60950-1) File E151273
Explosion protection	ATEX (EX) II 3G Ex nA II T4; cULus (ISA 12.12.01, CSA C22.2 No.213) Class I, Div. 2, Group ABCD, T4, File E330455
Certificate of suitability IECEx	No
Certificate of suitability NEC Class 2	No
FM approval	Class I, Div. 2, Group ABCD, T4
CB approval	Yes
Marine approval	GL, ABS, BV, DNV, LRS, NK
Degree of protection (EN 60529)	IP20

### EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	not applicable
Noise immunity	EN 61000-6-2

### Operating data

Ambient temperature during operation	0 ... 60 °C
• Note	with natural convection
Ambient temperature during transport	-40 ... +85 °C
Ambient temperature during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

### Mechanics

Connection technology	screw-type terminals
Connections Supply input	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm <sup>2</sup>
Connections Output	L+, M: 2 screw terminals each for 0.5 ... 2.5 mm <sup>2</sup>
Connections Auxiliary	-
Width of the enclosure	70 mm
Height of the enclosure	100 mm
Depth of the enclosure	75 mm
Weight, approx.	0.3 kg

Product property of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15, wall mounting
Other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)