

TRONIC-CY (LiY-CY)

flexible, colour coded to DIN 47100, screened, meter marking, EMC-preferred type



Technical data

- Special-PVC data cable adapted to DIN VDE 0812
- **Temperature range**
flexing -5°C to +80°C
fixed installation -40°C to +80°C
- **Operating peak voltage**
(not for heavy current installation purposes)
0,14 mm² 350 V
≥ 0,25 mm² 500 V
- **Test voltage**
core/core 1200 V
core/screen 800 V
- **Breakdown voltage**
min. 2400 V
- **Capacitance** at 800 Hz
core/core 0,14 mm² app. 120 pF/m
core/core 0,25 mm² app. 150 pF/m
core/screen 0,14 mm² app. 240 pF/m
core/screen 0,25 mm² app. 270 pF/m
- **Inductance**
approx. 0,65 mH/km
- **Impedance**
approx. 78 Ohm
- **Coupling resistance**
max. 250 Ohm/km
- **Minimum bending radius**
flexing 10x cable Ø
fixed installation 5x cable Ø
- **Radiation resistance**
up to 80x10⁶ cJ/kg (up to 80 Mrad)

Cable structure

- Bare copper conductor, from 0,5 mm² to DIN VDE 0295 cl.5, fine wire, BS 6360 cl.5, IEC 60228 cl.5
- Conductor construction:
0,14 mm² approx. 18x0,1 mm
0,25 mm² approx. 14x0,15 mm
0,34 mm² = 7x0,25 mm
- Core insulation of special PVC compound type T12 to DIN VDE 0207-363-3 / DIN EN 50363-3
- Core identification adapted to DIN 47100, without colour repetition
- Cores stranded in layers with optimal lay length
- Foil wrapping
- Drain-wire, tinned
- Tinned, copper braided screen, approx. 85% coverage
- Outer sheath of special PVC compound type TM2 to DIN VDE 0207-363-4-1 / DIN EN 50363-4-1
- Sheath colour: grey (RAL 7001)
- With meter marking

Properties

- Extensively oil resistant, oil-/chemical resistance see "Technical Informations"
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

Tests

- PVC self-extinguishing and flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1-2

Note

- Also available in paired version, see HELUKABEL®-PAAR-TRONIC-CY
- For 1 core cable screen of helically wound (LiY-DY).
- AWG sizes are approximate equivalent values. The actual cross section is in mm².
- Unscreened analogue type: **TRONIC (LiYY)**

Application

These screened cables are used for flexible use with free movement without tensile stress or forced movements in dry, moist and wet rooms but not suitable for open air, wherever the construction requirements call for a minimum outer diameter, TRONIC is the suitable cable to use. This applies especially to such areas as tool making and machine industries as well as electronic, computer, measurement and control sectors. The extremely small outer diameter make suitable for miniature plugs etc.

EMC = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
20139	1 x 0,14	2,6	6,1	16,0	26
20001	2 x 0,14	3,9	12,0	20,0	26
20002	3 x 0,14	4,0	13,0	27,0	26
20003	4 x 0,14	4,3	14,5	32,0	26
20004	5 x 0,14	4,7	15,5	37,0	26
20005	6 x 0,14	5,2	18,2	42,0	26
20006	7 x 0,14	5,2	19,0	48,0	26
20007	8 x 0,14	5,9	21,3	55,0	26
20008	10 x 0,14	6,5	28,7	65,0	26
20009	12 x 0,14	6,7	30,5	77,0	26
20010	14 x 0,14	6,9	32,0	79,0	26
20011	16 x 0,14	7,3	43,2	89,0	26
20012	18 x 0,14	7,6	51,0	103,0	26
20013	20 x 0,14	8,3	55,0	116,0	26

Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
20014	21 x 0,14	8,4	56,0	120,0	26
20015	24 x 0,14	8,9	62,0	131,0	26
20091	25 x 0,14	9,1	61,0	136,0	26
20016	27 x 0,14	9,2	65,0	142,0	26
20017	30 x 0,14	9,5	69,0	157,0	26
20018	32 x 0,14	9,9	76,0	163,0	26
20019	36 x 0,14	10,2	83,0	182,0	26
20020	40 x 0,14	11,1	88,0	209,0	26
20021	42 x 0,14	11,2	94,0	217,0	26
20022	44 x 0,14	11,5	110,0	226,0	26
20023	48 x 0,14	11,7	115,0	240,0	26
20024	52 x 0,14	12,3	124,0	270,0	26
20025	56 x 0,14	12,5	132,0	320,0	26
20026	61 x 0,14	12,8	146,0	370,0	26

Continuation ▶

TRONIC-CY (LiY-CY)

flexible, colour coded to DIN 47100, screened, meter marking, EMC-preferred type



Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.	Part no.	No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
20084	1 x 0,25	3,0	7,2	27,0	24	16012	16 x 0,5	10,6	129,0	210,0	20
20029	2 x 0,25	4,3	15,8	31,0	24	16013	18 x 0,5	11,3	152,0	217,0	20
20030	3 x 0,25	4,5	18,6	36,0	24	16526	19 x 0,5	11,3	156,0	246,0	20
20031	4 x 0,25	4,8	22,0	40,0	24	16014	20 x 0,5	12,0	173,0	275,0	20
20032	5 x 0,25	5,4	26,5	51,0	24	16015	24 x 0,5	13,2	236,0	337,0	20
20083	6 x 0,25	5,8	32,4	58,0	24	16016	25 x 0,5	13,7	250,0	351,0	20
20033	7 x 0,25	5,8	35,0	64,0	24	16527	27 x 0,5	13,8	265,0	373,0	20
20034	8 x 0,25	7,0	42,1	82,0	24	16017	30 x 0,5	14,2	297,0	396,0	20
20035	10 x 0,25	7,3	49,9	85,0	24	16018	32 x 0,5	14,7	301,0	431,0	20
20036	12 x 0,25	7,5	58,0	90,0	24	16164	34 x 0,5	15,4	312,0	440,0	20
20037	14 x 0,25	8,1	62,0	98,0	24	16019	36 x 0,5	15,5	320,0	445,0	20
20038	16 x 0,25	8,5	67,0	110,0	24	16528	37 x 0,5	15,5	325,0	458,0	20
20039	18 x 0,25	9,1	78,0	142,0	24	16020	40 x 0,5	16,4	345,0	470,0	20
20086	19 x 0,25	9,1	79,0	146,0	24	16021	50 x 0,5	18,2	407,0	570,0	20
20040	20 x 0,25	9,5	88,0	152,0	24	16022	61 x 0,5	19,2	508,0	650,0	20
20041	21 x 0,25	9,6	91,0	150,0	24	16025	1 x 0,75	4,0	19,0	41,0	19
20042	24 x 0,25	10,4	96,0	163,0	24	16026	2 x 0,75	5,8	38,0	59,0	19
20092	25 x 0,25	10,6	99,0	169,0	24	16027	3 x 0,75	6,3	50,0	66,0	19
20043	27 x 0,25	10,7	122,0	176,0	24	16028	4 x 0,75	6,8	57,0	77,0	19
20044	30 x 0,25	11,1	132,0	189,0	24	16029	5 x 0,75	7,4	70,0	93,0	19
20045	32 x 0,25	11,5	138,0	204,0	24	16030	6 x 0,75	8,2	87,0	113,0	19
20046	36 x 0,25	11,9	146,0	219,0	24	16031	7 x 0,75	8,2	96,0	130,0	19
20087	37 x 0,25	11,9	152,0	230,0	24	16032	8 x 0,75	9,7	110,0	145,0	19
20047	40 x 0,25	12,9	157,0	247,0	24	16033	10 x 0,75	10,3	140,0	180,0	19
20048	42 x 0,25	13,0	160,0	269,0	24	16034	12 x 0,75	10,5	151,0	202,0	19
20049	44 x 0,25	13,7	162,0	292,0	24	16035	14 x 0,75	11,3	167,0	225,0	19
20050	48 x 0,25	13,9	168,0	317,0	24	16036	16 x 0,75	11,9	183,0	275,0	19
20051	52 x 0,25	14,3	175,0	330,0	24	16037	18 x 0,75	12,7	207,0	292,0	19
20052	56 x 0,25	14,7	189,0	343,0	24	16529	19 x 0,75	12,7	221,0	322,0	19
20053	61 x 0,25	15,2	204,0	365,0	24	16038	20 x 0,75	13,6	238,0	362,0	19
20088	1 x 0,34	3,2	13,5	24,0	22	16039	24 x 0,75	14,9	270,0	435,0	19
20056	2 x 0,34	4,9	18,0	30,0	22	16040	25 x 0,75	15,0	278,0	415,0	19
20057	3 x 0,34	5,1	22,0	37,0	22	16041	27 x 0,75	15,1	287,0	467,0	19
20058	4 x 0,34	5,5	28,0	48,0	22	16042	30 x 0,75	16,0	315,0	486,0	19
20059	5 x 0,34	6,0	31,0	54,0	22	16043	32 x 0,75	16,5	330,0	530,0	19
20085	6 x 0,34	6,6	45,0	61,0	22	16163	34 x 0,75	17,1	350,0	570,0	19
20060	7 x 0,34	6,6	51,0	67,0	22	16044	36 x 0,75	17,4	370,0	600,0	19
20061	8 x 0,34	7,7	54,0	81,0	22	16530	37 x 0,75	17,4	386,0	640,0	19
20062	10 x 0,34	8,4	65,0	103,0	22	16045	40 x 0,75	18,7	395,0	680,0	19
20063	12 x 0,34	8,6	70,0	110,0	22	16120	42 x 0,75	18,9	408,0	714,0	19
20064	14 x 0,34	9,0	81,0	153,0	22	16047	61 x 0,75	22,0	555,0	900,0	19
20065	16 x 0,34	9,6	88,0	159,0	22	16475	2 x 1	6,4	46,0	65,0	18
20066	18 x 0,34	10,1	103,0	172,0	22	16476	3 x 1	6,7	56,0	80,0	18
20089	19 x 0,34	10,1	106,0	181,0	22	16477	4 x 1	7,2	69,0	98,0	18
20067	20 x 0,34	10,8	112,0	191,0	22	16478	5 x 1	8,0	89,0	127,0	18
20068	21 x 0,34	10,9	116,0	199,0	22	16479	6 x 1	8,7	105,0	144,0	18
20069	24 x 0,34	11,7	129,0	229,0	22	16480	7 x 1	8,7	111,0	158,0	18
20093	25 x 0,34	12,0	120,0	241,0	22	16481	8 x 1	10,3	130,0	197,0	18
20070	27 x 0,34	12,1	138,0	258,0	22	16482	10 x 1	11,2	140,0	232,0	18
20071	30 x 0,34	12,6	158,0	290,0	22	16483	12 x 1	11,4	168,0	260,0	18
20072	32 x 0,34	13,0	163,0	305,0	22	16484	14 x 1	12,0	198,0	302,0	18
20073	36 x 0,34	13,8	178,0	330,0	22	16485	16 x 1	12,8	218,0	346,0	18
20090	37 x 0,34	13,8	192,0	348,0	22	16486	19 x 1	13,6	268,0	412,0	18
20074	40 x 0,34	14,8	198,0	364,0	22	16487	24 x 1	16,0	320,0	493,0	18
20075	42 x 0,34	14,9	203,0	389,0	22	16488	27 x 1	16,4	360,0	562,0	18
20076	44 x 0,34	15,6	214,0	414,0	22	16489	37 x 1	18,6	485,0	790,0	18
20077	48 x 0,34	15,8	227,0	420,0	22	16500	2 x 1,5	7,0	63,0	88,0	16
20078	52 x 0,34	16,3	242,0	450,0	22	16501	3 x 1,5	7,4	76,0	100,0	16
20079	56 x 0,34	16,8	267,0	480,0	22	16502	4 x 1,5	8,1	98,0	126,0	16
20080	61 x 0,34	17,2	295,0	520,0	22	16503	5 x 1,5	9,0	116,0	160,0	16
16001	1 x 0,5	3,5	15,0	40,0	20	16504	6 x 1,5	9,8	140,0	192,0	16
16002	2 x 0,5	5,3	29,0	45,0	20	16505	7 x 1,5	9,8	152,0	208,0	16
16003	3 x 0,5	5,6	39,0	55,0	20	16506	8 x 1,5	11,0	172,0	244,0	16
16004	4 x 0,5	6,3	46,0	61,0	20	16507	10 x 1,5	12,6	193,0	315,0	16
16005	5 x 0,5	6,8	52,0	76,0	20	16508	12 x 1,5	12,8	254,0	338,0	16
16006	6 x 0,5	7,3	66,0	89,0	20	16509	14 x 1,5	13,5	272,0	383,0	16
16007	7 x 0,5	7,3	68,0	98,0	20	16510	16 x 1,5	14,6	285,0	424,0	16
16008	8 x 0,5	8,6	80,0	117,0	20	16511	19 x 1,5	15,6	387,0	506,0	16
16009	10 x 0,5	9,4	93,0	135,0	20	16512	24 x 1,5	18,1	448,0	690,0	16
16010	12 x 0,5	9,6	117,0	157,0	20	16513	27 x 1,5	18,7	506,0	781,0	16
16011	14 x 0,5	10,1	122,0	190,0	20	16514	37 x 1,5	21,4	682,0	941,0	16

Dimensions and specifications may be changed without prior notice. (RB01)