



**Panel mounted socket**  
screwless, with TwinCONTACT,  
flange: 75 x 75 mm, straight

▲ IP 44

A	P	110V	230V	400V
16	3	1667	1668	1669
16	4	1672	1673	1674
16	5	1678	1679	3385
32	3	1786	1787	1788
32	4	1789	1790	1791
32	5	1795	1796	1797



**Panel mounted socket**  
screwless, with TwinCONTACT,  
flange 16A, 3p: 73.5 x 64 mm,  
16A, 4 + 5p, 32A: 100 x 92 mm,  
20° inclination, 32A: optionally fitted  
with auxiliary contact

▲ IP 44

A	P	110V	230V	400V
16	3	1631	1632	1633
16	4	1636	1637	1638
16	5	1642	1643	3473
32	3	1733	1734	1735
32	4	1738	1739	1740
32	5	1744	1745	1746



**Panel mounted socket RAPIDO®**  
screwless, with TwinCONTACT,  
with central locking system, round flange  
for central fixing, diam. 70 mm

▲ IP 44

A	P	110V	230V	400V
16	4		1133	998
16	5			907
32	3	1135	987	
32	4		1166	988
32	5			989



**Panel mounted socket**  
screwless, with TwinCONTACT,  
flange: 16A: 75 x 75 mm,  
32A: 85 x 75 mm, straight

▲▲ IP 67

A	P	110V	230V	400V
16	3	1707	1708	1709
16	4	1710	1711	1712
16	5	1716	1717	1131
32	3	1809	1810	1811
32	4	1812	1813	1814
32	5	1818	1819	1820



**Panel mounted socket**  
screwless, with TwinCONTACT,  
flange: 16A, 3p: 73.5 x 64 mm,  
16A, 4 + 5p, 32A: 100 x 92 mm,  
20° inclination, 32A: optionally fitted with  
auxiliary contact (Part no. 41000)

▲▲ IP 67

A	P	110V	230V	400V
16	3	1700	1701	1702
16	4		1703	1704
16	5			3485
32	3	1801	1802	1803
32	4		1804	1805
32	5			1808



**Panel mounted socket**  
screwless, with TwinCONTACT,  
standard flange dimensions 85 x 85 mm,  
20° inclination, optionally fitted with  
auxiliary contact

▲▲ IP 67

A	P	110V	230V	400V
16	3	1158	1168	
16	4			1169
16	5			1173
32	3	3566	3573	
32	4			3581
32	5			3590