



Main

Range	Acti 9
Product or component type	OC and fault contact
Device short name	OF and SD
Signal contacts composition	2 C/O
9 mm pitches	1

Complementary

[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-5-1
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-5-1
Mounting mode	Fixed
Mounting support	DIN rail
Height	103 mm
Width	18 mm
Depth	69 mm
Electrical durability	10000 cycles conforming to EN/IEC 60947-5-1
Connections - terminals	Plate terminal 2 flexible cable(s) 1.5 mm ² max Plate terminal 1 flexible cable(s) 2.5 mm ² max Plate terminal 2 rigid cable(s) 1.5 mm ² max Plate terminal 1 rigid cable(s) 2.5 mm ² max
Wire stripping length	10 mm
Tightening torque	1 N.m
Product compatibility	NG125

Environment

Standards	EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.