



Main

Device short name	Interpact INS63
Switch-disconnector name	Interpact INS63
Poles description	4P
Network type	AC DC
Network frequency	50/60 Hz
[Ie] rated operational current	40 A AC-23A AC 50/60 Hz 500 V 63 A AC-22A AC 50/60 Hz 220/240 V 63 A AC-23A AC 50/60 Hz 220/240 V 63 A AC-22A AC 50/60 Hz 380/415 V 63 A AC-23A AC 50/60 Hz 380/415 V 63 A AC-22A AC 50/60 Hz 440/480 V 63 A AC-23A AC 50/60 Hz 440/480 V 63 A AC-22A AC 50/60 Hz 500 V 63 A DC-22A DC 125 V 2 poles in series 63 A DC-23A DC 125 V 2 poles in series 63 A DC-22A DC 250 V 4 poles in series 63 A DC-23A DC 250 V 4 poles in series 63 A AC-22A AC 50/60 Hz 480 V NEMA 63 A AC-23A AC 50/60 Hz 480 V NEMA
[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	63 A 60 °C
[Icm] rated short-circuit making capacity	15 kA switch-disconnector alone 500 V AC 50/60 Hz 75 kA with upstream protection circuit breaker 500 V AC 50/60 Hz
[Ue] rated operational voltage	250 V DC 500 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No
Pollution degree	3

Complementary

Control type	Rotary handle
Mounting mode	Fixed
Mounting support	DIN rail plate
Upside connection	Front
Downside connection	Front
Cable cross section	1,5...50 mm ²
Maximum power	15 kW AC-23 230 V NEMA AC 50/60 Hz 15 kW AC-23 220/240 V AC 50/60 Hz 22 kW AC-23 500/525 V AC 50/60 Hz 30 kW AC-23 380/415 V AC 50/60 Hz 30 kW AC-23 440 V AC 50/60 Hz 30 kW AC-23 480 V NEMA AC 50/60 Hz
Rated duty	Uninterrupted
Intermittent duty class	Class 120 - 60 %
Enclosure dimensions for lthe	190 mm x 115 mm x 55 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

[I _{cw}] rated short-time withstand current	3 kA 1 s IEC 60947-3 5,5 kA 30 s IEC 60947-3 0,067 kA 20 s IEC 60947-3 1,73 kA 3 s IEC 60947-3
Mechanical durability	20000 cycles
Electrical durability	1500 cycles 220/240 V AC 50/60 Hz AC-22A 1500 cycles 220/240 V AC 50/60 Hz AC-23A 1500 cycles 380/415 V AC 50/60 Hz AC-22A 1500 cycles 380/415 V AC 50/60 Hz AC-23A 1500 cycles 440 V AC 50/60 Hz AC-22A 1500 cycles 440 V AC 50/60 Hz AC-23A 1500 cycles 500 V AC 50/60 Hz AC-22A 1500 cycles 500 V AC 50/60 Hz AC-23A 1500 cycles 250 V 4 poles in series DC DC-22A 1500 cycles 250 V 4 poles in series DC DC-23A
Connection pitch	18 mm
Height	85 mm
Width	90 mm
Depth	62,5 mm
Product weight	0,6 kg

Environment

Standards	IEC 60947-1 IEC 60947-3
Product certifications	CCC KEMA-KEUR
IP degree of protection	IP40 IEC 60529
IK degree of protection	IK07 EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
RoHS EUR conformity date	0815
RoHS EUR status	Compliant