



Main

Range of product	PratiKa
Product or component type	Interlocked socket
Device short name	Unika socket
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

Complementary

Mounting mode	Wall-mounted
[In] rated current	16 A
[Ue] rated operational voltage	200...250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Protection type	Without protection
Plug, socket material	Self-extinguishing engineering polymer housing:
Contacts material	Nickel plated brass sleeves:
Connections - terminals	Captive screws
Cable cross section	<= 10 mm ²
Cable outer diameter	<= 25 mm
Cable entry	Cable gland
Thread type	Pg 21
Product weight	0.96 kg
Base dimension	103 x 255 mm
Height	255 mm
Width	103 mm
Depth	149 mm
Colour	Grey (RAL 7035)
Voltage colour	Blue

Environment

Standards	IEC 60309-1 IEC 60309-2
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 62262
Fire resistance	750 °C conforming to IEC 60695-2-11
Relative humidity	90 % (20 °C) 70 % (30 °C) 50 % (40 °C)
Ambient air temperature for operation	-25...40 °C 35 °C (86400 s)

Contractual warranty

Period	18 months
--------	-----------