



Main

| | |
|---------------------------|---------------------------|
| Range | ZENcelo |
| Product or component type | Switch |
| Local signalling | Indicator light LED amber |
| Number of gangs | 1 gang |
| Colour tint | Bronze |

Complementary

| | |
|-------------------------|---|
| Device mounting | Flush Surface |
| Switch function | 2-way |
| Number of cables | 1...2 4 mm ² solid 1...2 2.5 mm ² stranded 1...2 2.5 mm ² solid 1...2 1.5 mm ² stranded 1...2 1.5 mm ² solid |
| Rated current | 16 AX 250 V AC 50/60 Hz |
| Material | Polycarbonate lenses Polycarbonate + GF 20 % actuator Polycarbonate driver Polycarbonate dolly Polycarbonate base Brass metal parts |
| Load type | Capacitive Inductive Resistive |
| Connections - terminals | Clamp terminal |
| Width | 34.85 mm |
| Height | 45.8 mm |
| Depth | 32.8 mm |

Environment

| | |
|---------------------------------------|---------------------------|
| Ambient air temperature for operation | -5...45 °C |
| Ambient air temperature for storage | -5...60 °C |
| Relative humidity | 0...95 % |
| Environmental characteristic | UV resistant |
| Operating altitude | 2000 m |
| Product certifications | CCC |
| Standards | GB 16915.1 IEC 60669-1 |
| IP degree of protection | IP20 |