



### Main

Range	ZENcelo
Product or component type	Switch
Local signalling	Indicator light LED amber
Number of gangs	1 gang
Colour tint	Bronze

### Complementary

Device mounting	Flush Surface
Switch function	Intermediate
Number of cables	1...2 4 mm <sup>2</sup> stranded 1...2 4 mm <sup>2</sup> solid 1...2 2.5 mm <sup>2</sup> stranded 1...2 2.5 mm <sup>2</sup> solid 1...2 1.5 mm <sup>2</sup> stranded 1...2 1.5 mm <sup>2</sup> solid
Rated current	16 AX 250 V AC 50/60 Hz
Material	Polycarbonate lenses Polycarbonate + GF 20 % actuator Polycarbonate driver Steel metal parts Polycarbonate dolly Polycarbonate base Copper metal parts
Load type	Fluorescent lamp Resistive
Connections - terminals	Clamp terminal
Width	34.85 mm
Height	45.8 mm
Depth	32.8 mm

### Environment

Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	2000 m
Product certifications	BSMI CCC BPS
Standards	GB 16915.1 IEC 60669-1
IP degree of protection	IP20