

Main

Product or component type	Power socket-outlet
Rated current	16 A 250 V AC 50 Hz
Cover plate colour tint	Bronze

Complementary

Device mounting	Flush Surface
Outlet poles configuration	2P + E universal
Number of cables	1...2 2.5 mm ² stranded 1...2 2.5 mm ² solid 1...2 4 mm ² stranded 1...2 4 mm ² solid
Number of gangs	2 gangs
Material	Polycarbonate cover Polycarbonate base
Load type	Inductive Resistive
Connections - terminals	Screw terminals
Width	46 mm
Height	70.1 mm
Depth	30.5 mm

Environment

Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	10...95 % non-condensing operating 0...95 % non-condensing storage
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
IP degree of protection	IP20
Standards	IEC 60364 IEC 60884-1
Product certifications	TISI

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.