

# CA2KN22M7

contactor TeSys CA2-K - 2 NO + 2 NC -  
instantaneous - 10 A - 220...230 V AC



## Main

Range of product	TeSys k control relay
Product or component type	Electromagnetic relay
Device short name	CA2K
Contactors application	Control circuit
Utilisation category	AC-15
Control circuit type	AC
Coil type	Standard
Coil technology	Without integral suppression device
Pole contact composition	2 NO + 2 NC
[Uc] control circuit voltage	220/230 V AC 50/60 Hz
Connections - terminals	Screwclamp terminal 1 cable 0.34...1.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Screwclamp terminal 1 cable 0.34...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Screwclamp terminal 1 cable 0.75 mm <sup>2</sup> - cable stiffness: flexible - without cable end Screwclamp terminal 1 cable 1.5 mm <sup>2</sup> - cable stiffness: solid Screwclamp terminal 2 cable 4 mm <sup>2</sup> - cable stiffness: flexible - without cable end Screwclamp terminal 2 cable 4 mm <sup>2</sup> - cable stiffness: solid

## Complementary

Contact operation	Mechanically linked conforming to IEC 60947-5-1
Control circuit voltage limits	$\leq 0.2 U_c$ at 50 °C drop-out 50/60 Hz $0.8...1.15 U_c$ at 50 °C operational 50/60 Hz
[Ui] rated insulation voltage	600 V - conforming to CSA C22-2 No 14 690 V - conforming to BS 5424 690 V - conforming to IEC 60947 750 V - conforming to VDE 0110 group C
Flame retardance	Class C2 conforming to NF F 16-101 Class C2 conforming to NF F 16-102 V1 conforming to UL 94
Tightening torque	0.8...1.3 N.m - on screwclamp terminal - with screwdriver flat $\varnothing$ 6 mm 0.8...1.3 N.m - on screwclamp terminal - with screwdriver Philips 2 mm
[Ue] rated operational voltage	$\leq 690$ V AC $\leq 400$ Hz
[Ith] conventional free air thermal current	10 A at $\leq 50$ °C
Irms rated making capacity	110 A at $\leq 690$ V AC conforming to IEC 60947
Associated fuse rating	10 A gG at $\leq 690$ V conforming to IEC 60947 10 A gG at $\leq 690$ V conforming to VDE 0660
Inrush power in VA	30 VA at 20 °C
Hold-in power consumption in VA	4.5 VA at 20 °C 50/60 Hz
Mechanical durability	10000000 cycles
Operating rate	10000 cyc/h at 20 °C
Operating time	10...20 ms coil de-energisation and NO opening 10...20 ms coil energisation and NO closing 15...25 ms coil de-energisation and NC closing 5...15 ms coil energisation and NC opening
Minimum switching current	5 mA
Minimum switching voltage	17 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Non-overlap time	1.5 ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts
Non overlap distance	0.5 m
Insulation resistance	> 10 MOhm
Height	58 mm
Width	45 mm
Depth	57 mm
Product weight	0.18 kg

## Environment

Standards	BS 5424 IEC 60947 NF C 63-140 VDE 0660
Product certifications	CSA UL
IP degree of protection	IP2x conforming to VDE 0106
Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-50...80 °C
Operating altitude	2000 m without derating in temperature
Shock resistance	10 gn control relay open 15 gn control relay closed
Vibration resistance	2 gn 5...300 Hz control relay open 4 gn 5...300 Hz control relay closed
Heat dissipation	1.3 W at 50/60 Hz
Immunity to microbreaks	2 ms