

Product datasheet

Specifications



AvatarOn, USB charger, 2 type A, 2.1 A, White

E8332USB_WE

Main

Product or component type	USB charger
Integrated connection type	2 USB type A 5 V DC, maximum load current: 2.1 A

Complementary

Device mounting	Flush
Device presentation	Complete product
Colour tint	White
Surface finish	Glossy
[Ue] rated operational voltage	100/240 V AC 50/60 Hz
Maximum load current with 2 outputs used simultaneously	2.1 A
Material	PC (polycarbonate)
Connections - terminals	Screw terminals
Screwdriver shape	Phillips combined
Clamping connection capacity	1.5...2.5 mm ² for flexible cable(s) 1.5...2.5 mm ² for rigid cable(s)
Height	86 mm
Width	86 mm
Depth	40 mm

Environment

Standards	IEC 60950-1
Electrical insulation class	Class II
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	104 g
Package 1 Height	3.4 cm
Package 1 width	8.6 cm

Package 1 Length	8.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	882 g
Package 2 Height	9.5 cm
Package 2 width	19 cm
Package 2 Length	19.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile