

Product datasheet

Specifications



AvatarOn, socket-outlet, 16A, 2 x 3P, universal, White

E83426UES2_WE

Main

Product or component type	Socket-outlet
Device presentation	Complete product
Load type	Resistive Inductive
Colour tint	White
Outlet poles configuration	2 x 3P
Outlet standard	Universal

Complementary

Rated current	16 A at 250 V AC 50 Hz
Socket number	2
Clamping connection capacity	1 x 4...2 x 4 mm ² for solid cable(s) 1 x 4...2 x 4 mm ² for stranded cable(s) 1 x 2.5...2 x 2.5 mm ² for solid cable(s) 1 x 2.5...2 x 2.5 mm ² for stranded cable(s)
Connections - terminals	Brass pillar Folded terminal
Material	Polycarbonate grid plate Polycarbonate surround
Device mounting	Surface Flush
Width	86 mm
Height	86 mm
Depth	26.7 mm
Embedding depth	17 mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	35 °C
Ambient air temperature for storage	-5...45 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant

Operating altitude	5000 m
Standards	IEC 60884-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	100 g
Package 1 Height	4.5 cm
Package 1 width	8.5 cm
Package 1 Length	8.5 cm
SCC14	23606481455215
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1 kg
Package 2 Height	9.5 cm
Package 2 width	15 cm
Package 2 Length	19 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Weight	6 kg
Package 3 Height	21 cm
Package 3 width	30 cm
Package 3 Length	39.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile