

E8431-1_SA

16AX/20A 1 Gang 1 Way Full-Flat Switch with Indicator, Silver Satin



Main

Range of product	ZENcelo
Product or component type	Switch
Local signalling	Mechanical indicator amber
Number of gangs	1 gang
Cover frame colour tint	Silver satin

Complementary

Wiring device mounting	Flush Surface
Switch function	1-way
Number of cables	3 2.5 mm ² solid 3 2.5 mm ² stranded 4 1.5 mm ² solid 4 1.5 mm ² stranded
Rated current	20 A 250 V AC 50/60 Hz
Material	Polycarbonate surround Polycarbonate base Polycarbonate cover Polycarbonate + GF 20 % grid plate
Load type	Fluorescent lamp Incandescent lamp Inductive Resistive
Connections - terminals	Brass rod terminals
Width	87 mm
Height	87 mm
Depth	31 mm

Environment

Ambient air temperature for operation	≤ 35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	EN 60669-1 GB 16915.1 IEC 60669-1 MS IEC 60669-1 SS 227-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.