

# Product datasheet

Specifications



## Kavacha - 55A - 440V - Surface Mount triple Pole Isolating Switch - IP66

WHT55\_GY

### Main

Range	Kavacha
Product or component type	Isolating switch
Device short name	W
Device application	Control

### Complementary

[Ie] rated operational current	55 A at 440 V AC-22A
Poles description	3P
Motor Rating	M160
Width	82 mm
Height	170 mm
Depth	90 mm

### Environment

IP degree of protection	IP66
Standards	IEC 60947-3
Environmental characteristic	Weatherproof

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	733.333 g
Package 1 Height	17.5 cm
Package 1 width	9 cm
Package 1 Length	8.3 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	30
Package 2 Weight	22000 g
Package 2 Height	365 mm
Package 2 width	285 mm

<b>Package 2 Length</b>	435 mm
<b>Unit Type of Package 3</b>	P12
<b>Number of Units in Package 3</b>	540
<b>Package 3 Weight</b>	414000 g
<b>Package 3 Height</b>	1300 mm
<b>Package 3 width</b>	800 mm
<b>Package 3 Length</b>	1200 mm

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>