

# Product datasheet

Specifications



contact block - XKB - for use with zero (center) position interlocking handle

Local distributor code: 395514887 XKBZ969

## Main

|  |   |
|--|---|
| <b>Product or component type</b>                         | Controllers separate parts                              |
| <b>Accessory / separate part category</b>                | Control accessory                                       |
| <b>Product specific application</b>                      | Light hoisting applications                             |
| <b>Product compatibility</b>                             | XKB   |
| <b>Accessory / separate part type</b>                    | Contacts block  |
| <b>Accessory / separate part specific characteristic</b> | For use with zero (center) position interlocking handle |

## Complementary

|   |   |
|---|---|
| <b>Contact block per direction [control circuit]</b>          | 4 per movement<br>1 zero (center) position  |
| <b>Electrical connection</b>                                  | Screw clamp terminal, clamping capacity: 1 x 0.5...1 x 1.5 mm <sup>2</sup><br>Screw clamp terminal, clamping capacity: 1 x 0.5...1 x 2.5 mm <sup>2</sup>  |
| <b>Enclosure/Cubicle description</b>                          | Monobloc  |
| <b>Contacts type and composition</b>                          | 8 NO<br>1 NC  |
| <b>Contact operation</b>                                      | Slow-break<br>Double-break  |
| <b>[I<sub>th</sub>] conventional free air thermal current</b> | 10 A conforming to IEC 337-1<br>10 A conforming to NF C 63-140<br>10 A conforming to VDE 0660<br>10 A conforming to CSA C22.2 No 14   |
| <b>[U<sub>i</sub>] rated insulation voltage</b>               | 500 V AC/DC conforming to IEC 158-1<br>500 V AC/DC conforming to NF C 20-040<br>500 V AC/DC conforming to VDE 0110  |
| <b>Maximum resistance across terminals</b>                    | 25 mOhm at 1 A conforming to NF C 93-050  |
| <b>Positive opening</b>                                       | With<br>Without   |
| <b>Short-circuit protection</b>                               | 10 A cartridge fuse type gG conforming to IEC 337-1B<br>10 A cartridge fuse type gG conforming to VDE 0660 part 2   |
| <b>Electrical durability</b>                                  | 1000000 cycles DC inductive load at 120 V, power broken = 75 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5<br>1000000 cycles DC inductive load at 24 V, power broken = 90 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5<br>1000000 cycles DC inductive load at 48 V, power broken = 90 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5 |
| <b>Net weight</b>   | 0.215 kg  |

## Environment

---

|           |                  |
|-----------|------------------|
| Standards | CENELEC EN 50013 |
|-----------|------------------|

---

## Packing Units

---

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

---

|                              |   |
|------------------------------|---|
| Number of Units in Package 1 | 1 |
|------------------------------|---|

---

|                  |         |
|------------------|---------|
| Package 1 Weight | 171.9 g |
|------------------|---------|

---

|                  |        |
|------------------|--------|
| Package 1 Height | 3.5 cm |
|------------------|--------|

---

|                 |        |
|-----------------|--------|
| Package 1 width | 9.2 cm |
|-----------------|--------|

---

|                  |        |
|------------------|--------|
| Package 1 Length | 9.2 cm |
|------------------|--------|

---

|                        |     |
|------------------------|-----|
| Unit Type of Package 2 | S01 |
|------------------------|-----|

---

|                              |    |
|------------------------------|----|
| Number of Units in Package 2 | 10 |
|------------------------------|----|

---

|                  |          |
|------------------|----------|
| Package 2 Weight | 1.916 kg |
|------------------|----------|

---

|                  |       |
|------------------|-------|
| Package 2 Height | 15 cm |
|------------------|-------|

---

|                 |       |
|-----------------|-------|
| Package 2 width | 15 cm |
|-----------------|-------|

---

|                  |       |
|------------------|-------|
| Package 2 Length | 40 cm |
|------------------|-------|

---

## Offer Sustainability

---

|                   |   |
|-------------------|---|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
|-------------------|---|

---

|              |     |
|--------------|-----|
| Mercury free | Yes |
|--------------|-----|

---

|                            |                     |
|----------------------------|---------------------|
| RoHS exemption information | <a href="#">Yes</a> |
|----------------------------|---------------------|

---

|                       |  |
|-----------------------|--|
| China RoHS Regulation | <a href="#">China RoHS declaration</a> |
|-----------------------|--|

---

|      |   |
|------|---|
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
|------|---|

---

## Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---