

Main

Range of product	Harmony XB4
Cap/Operator or lens colour	Green
Operator additional information	With plain lens
Product or component type	Head for pilot light
Product compatibility	BA 9s
Device short name	ZB4
Bezel material	Chromium plated metal
Mounting diameter	22 mm
Sale per indivisible quantity	1
IP degree of protection	IP66 IEC 60529
Shape of signaling unit head	Round

Complementary

Product weight	0,027 kg
Resistance to high pressure washer	7000000 Pa 55 °C 0.1 m

Environment

Protective treatment	TH
Shock resistance	30 gn 18 ms half sine wave acceleration IEC 60068-2-27 50 gn 11 ms half sine wave acceleration IEC 60068-2-27
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
Class of protection against electric shock	Class I IEC 60536
NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK05 IEC 50102
Standards	CSA C22-2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508
Vibration resistance	5 gn 2...500 Hz IEC 60068-2-6
RoHS EUR conformity date	0627
RoHS EUR status	Compliant