

### Main

|                                 |                       |
|---------------------------------|-----------------------|
| Range of product                | Harmony XB4           |
| Cap/Operator or lens colour     | Green                 |
| Operator additional information | With plain lens       |
| Product or component type       | Head for pilot light  |
| Product compatibility           | Integral LED          |
| Device short name               | ZB4                   |
| Bezel material                  | Chromium plated metal |
| Mounting diameter               | 22 mm                 |
| Sale per indivisible quantity   | 1                     |
| IP degree of protection         | IP66 IEC 60529        |
| Shape of signaling unit head    | Round                 |

### Complementary

|                                    |                        |
|------------------------------------|------------------------|
| Product weight                     | 0,026 kg               |
| Resistance to high pressure washer | 7000000 Pa 55 °C 0.1 m |

### Environment

|  |   |
|--|---|
| Protective treatment                       | TH  |
| Shock resistance                           | 30 gn 18 ms half sine wave acceleration IEC 60068-2-27<br>50 gn 11 ms half sine wave acceleration IEC 60068-2-27      |
| Ambient air temperature for storage        | -40...70 °C   |
| Ambient air temperature for operation      | -25...70 °C   |
| Class of protection against electric shock | Class I IEC 60536   |
| NEMA degree of protection                  | NEMA 13<br>NEMA 4X  |
| IK degree of protection                    | IK05 IEC 50102  |
| Standards                                  | CSA C22-2 No 14<br>EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-5<br>JIS C 4520<br>UL 508 |
| Vibration resistance                       | 5 gn 2...500 Hz IEC 60068-2-6   |
| RoHS EUR conformity date                   | 0627  |
| RoHS EUR status                            | Compliant   |