



Main

Range of product	AvatarOn A
Product or component type	Socket-outlet
Device presentation	Complete product
Colour tint	Black
Outlet poles configuration	2P + E

Complementary

Rated current	16 A at 250 V AC 50...60 Hz
Socket number	1
Clamping connection capacity	2 x 1.5...2 x 4 mm ² for solid cable(s) 2 x 1.5...2 x 4 mm ² for stranded cable(s)
Connections - terminals	Screwless terminals
Material	Polycarbonate grid plate Polycarbonate cover
Device mounting	Flush
Width	120 mm
Height	70 mm
Depth	30.3 mm
Embedding depth	19 mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	35 °C
Ambient air temperature for storage	-5...45 °C
Relative humidity	0...95 %
Operating altitude	< 2000 m

Standards	IEC 60884-1
Product certifications	IEC

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile