



### Main

Range of product	AvatarOn A
Product or component type	Socket-outlet
Device presentation	Complete product
Colour tint	White
Outlet poles configuration	2P + E

### Complementary

Rated current	16 A at 250 V AC 50...60 Hz
Socket number	1
Clamping connection capacity	2 x 1.5...2 x 4 mm <sup>2</sup> for solid cable(s) 2 x 1.5...2 x 4 mm <sup>2</sup> for stranded cable(s)
Connections - terminals	Screwless terminals
Material	Polycarbonate grid plate Polycarbonate cover
Device mounting	Flush
Width	120 mm
Height	70 mm
Depth	30.3 mm
Embedding depth	19 mm

### Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	35 °C
Ambient air temperature for storage	-5...45 °C
Relative humidity	0...95 %
Operating altitude	< 2000 m

Standards	IEC 60884-1
Product certifications	IEC

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>