



Main

Range	Acti 9
Product name	Acti 9 iPRD PV-DC
Device short name	IPRD PV-DC
Product or component type	Surge arrester with pluggable cartridge
Poles description	2P
Output type	Contact (volt-free)
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network

Complementary

Surge arrester class type	Type 2
Surge arrester technology	MOV
[Ue] rated operational voltage	1000 V (+/- 10 %) DC
Nominal discharge current	15 kA
Maximum discharge current	40 kA
[Uc] maximum continuous operating voltage	Differential mode : 1000 V L+/L- Common mode : 1000 V L-/PE
[Up] voltage protection level	3.9 kV type 2 common mode L+/PE 3.9 kV type 2 common mode L-/PE 3.9 kV type 2 differential mode L+/L-
Disconnecter device type	Associated circuit breaker iC60H 50 A Icu 15 kA curve C
Local signalling	Flag color: white/red
Signalling circuit voltage	AC : 250 V 50/60 Hz
Signalling output current	0.25 A
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	85 mm

Width	54 mm
Depth	70 mm
Product weight	0.342 kg
Colour	White (RAL 9003)
Response time	<= 25 ns
Connections - terminals	Tunnel type terminal upside 2.5...35 mm ² Tunnel type terminal downside 2.5...35 mm ²
Tightening torque	2.5 N.m

Environment

Standards	EN 50539-11 : 2013 UTE C 61740-51
Product certifications	CE
IP degree of protection	On front face : IP40 On terminal : IP20
IK degree of protection	IK03
Relative humidity	5...90 %
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1304 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------