



Main

Range of product	Phaseo Universal
Product or component type	Power supply
Power supply type	Regulated switch mode
Rated power in W	240 W
Input voltage	100...120 V AC single phase N-L1 200...500 V AC phase to phase L1-L2
PFC filter	With IEC 61000-3-2
Output voltage	24 V DC
Power supply output current	10 A
Output protection type	Against overload manual or automatic reset Against overvoltage 30...32 V, manual reset Against short-circuits manual or automatic reset Against undervoltage tripping if $U < 21.6$ V Thermal automatic reset

Complementary

Input voltage limits	85...132 V 170...550 V
Network frequency limits	47...63 Hz
Inrush current	≤ 30 A 2 ms
Cos phi	0,68 240 V 0,69 120 V
Efficiency	> 87 %
Power dissipation in W	31 W
Output voltage limits	24...28.8 V adjustable
Line and load regulation	1...3 %
Residual ripple	≤ 200 mV
Holding time	≥ 120 ms 400 V ≥ 20 ms 100 V ≥ 40 ms 240 V
Permissible temporary current boost	1.5 x I_n for 4 s
Connections - terminals	Removable screw terminal block diagnostic relay 2 x 2.5 mm ² Screw type terminals input connection 3 x 0.5...3 x 4 mm ² 22...12 Screw type terminals input ground connection 1 x 0.5...1 x 4 mm ² 22...12 Screw type terminals output connection 4 x 0.5...4 x 4 mm ² 22...12 Screw type terminals output ground connection 1 x 0.5...1 x 4 mm ² 22...12
Marking	CE
Mounting support	35 x 15 mm symmetrical DIN rail 35 x 7.5 mm symmetrical DIN rail
Operating position	Vertical
Output coupling	Parallel series
Name of test	Conducted emissions on the power line EN 55022 Class B GL level Electrostatic discharges EN/IEC 61000-4-2 Harmonic current emission EN/IEC61000-3-2 Induced electromagnetic field EN/IEC 61000-4-6 level 3 Magnetic field EN 61000-4-8 Primary outage IEC 61000-4-11 Radiated electromagnetic field EN/IEC 61000-4-3 level 3 Radiated emissions EN 55022 Class B GL level Rapid transient IEC 61000-4-4 Surge EN/IEC 61000-4-5

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Status LED	1 LED green, red and orange output current 1 LED green and red output voltage
Product weight	1 kg

Environment

Product certifications	C-Tick UL cCSAus
Environmental characteristic	EMC EN 61000-6-1 EMC EN/IEC 61000-6-2 EMC EN 61000-6-3 EMC EN/IEC 61000-6-4 EMC EN/IEC 61204-3 Safety EN/IEC 60950-1 Safety EN/IEC 61204-3 Safety SELV
IP degree of protection	IP20 EN/IEC 60529
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C
Relative humidity	0...90 % during operation 0...95 % in storage
Class of protection against electric shock	Class I VDE 0106-1
Vibration resistance	2 gn 11,9...150 Hz EN/IEC 61131-2 3.5 mm 3...11,9 Hz EN/IEC 61131-2
Dielectric strength	500 V between output and ground 3500 V between input and ground 4000 V between input and output
RoHS EUR conformity date	0501
RoHS EUR status	Compliant