



Main

Range of product	E3000
Product or component type	Key card switch
Bulb type	LED, blue
Rated current	16 A at 250 V AC 50/60 Hz
Colour tint	Grey silver

Complementary

Wiring device mounting	Flush Surface
Material	Brass: metal parts Polycarbonate: plastic part Steel: metal parts
Load type	Resistive
Clamping connection capacity	1 x 4 mm ² for stranded cable(s) 2 x 4 mm ² for stranded cable(s) 1 x 2.5 mm ² for solid cable(s) 1 x 2.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s) 2 x 2.5 mm ² for stranded cable(s) 3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 Mm
Height	87 Mm
Depth	25 Mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	GB 16915.2 IEC 60669-2-1

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	Download RoHS China Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Product Life Status : **Commercialised**