



Main

| | |
|---------------------------|---|
| Range | AvatarOn |
| Product or component type | Switch |
| Device application | Control |
| Load type | Fluorescent lamp Incandescent lamp Inductive Resistive |
| Colour tint | Wine gold |

Complementary

| | |
|------------------------------|--|
| Rated current | 16 AX 250 V AC 50/60 Hz |
| Switch function | 2-way |
| Number of gangs | 1 gang |
| Clamping connection capacity | 3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s) |
| Connections - terminals | Brass terminal |
| Material | Polycarbonate + GF 20 % actuator Polycarbonate frame Polycarbonate base Polycarbonate dolly Polycarbonate grid plate |
| Device mounting | Flush Surface |
| Width | 86 mm |
| Height | 86 mm |
| Depth | 34.2 mm |

Environment

| | |
|---------------------------------------|--------------|
| Ambient air temperature for operation | <= 45 °C |
| Relative humidity | 0..95 % |
| Environmental characteristic | UV resistant |
| Operating altitude | 2000 m |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.