



### Main

Range of product	GV2L GV2LE GV2ME GV2P GV3L GV3P GV2RT
Product or component type	Auxiliary contact block
Auxiliary contacts operation	Fault signal Instantaneous
Pole contact composition	2 NO
Connections - terminals	Control circuit: screw clamps terminals 1 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid Control circuit: screw clamps terminals 1 cable 0.75...2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end Control circuit: screw clamps terminals 2 cable 0.75...1.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Control circuit: screw clamps terminals 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid Control circuit: screw clamps terminals 1 cable 0.75...1.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Control circuit: screw clamps terminals 2 cable 0.75...2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end

### Complementary

Mounting location	Left side
[Ui] rated insulation voltage	300 V - for control circuit - conforming to CSA C22-2 No 14 300 V - for control circuit - conforming to UL 508 690 V - for control circuit - conforming to IEC 60947-1
[Ue] rated operational voltage	110 V DC for control circuit 110...127 V AC for control circuit 230...240 V AC for control circuit 24 V AC for control circuit 24 V DC for control circuit 240 V DC for control circuit 380...415 V AC for control circuit 440 V AC for control circuit 48 V AC for control circuit 48 V DC for control circuit 500 V AC for control circuit 60 V DC for control circuit 690 V AC for control circuit
[Ith] conventional free air thermal current	1 A for control circuit conforming to CSA C22-2 No 14 1 A for control circuit conforming to UL 508 5 A for control circuit conforming to CSA C22-2 No 14 5 A for control circuit conforming to UL 508 6 A for control circuit conforming to IEC 60947-5-1 2.5 A for control circuit conforming to IEC 60947-5-1
Protection type	GB2CB... circuit breaker rating according to operational current for Ue ≤ 415 V for control circuit GG fuse ≤ 10 A for control circuit
Mechanical durability	100000 cycles
Minimum switching current	5 mA for control circuit
Minimum switching voltage	17 V for control circuit
Rated operational power in VA	300 VA at 48 V AC-15 - electrical durability: 100000 cycles - for control circuit 36 VA at 24 V AC-14 - electrical durability: 1000 cycles - for control circuit 400 VA at 690 V AC-15 - electrical durability: 100000 cycles - for control circuit 48 VA at 48 V AC-14 - electrical durability: 1000 cycles - for control circuit 500 VA at 500 V AC-15 - electrical durability: 100000 cycles - for control circuit

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

650 VA at 440 V AC-15 - electrical durability: 100000 cycles - for control circuit  
500 VA at 110...127 V AC-15 - electrical durability: 100000 cycles - for control circuit  
720 VA at 230...240 V AC-15 - electrical durability: 100000 cycles - for control circuit  
850 VA at 380...415 V AC-15 - electrical durability: 100000 cycles - for control circuit  
72 VA at 110...127 V AC-14 - electrical durability: 1000 cycles - for control circuit

---

Rated operational power in W	120 W at 240 V DC-13 - electrical durability: 100000 cycles - for control circuit 140 W at 110 V DC-13 - electrical durability: 100000 cycles - for control circuit 140 W at 24 V DC-13 - electrical durability: 100000 cycles - for control circuit 15 W at 48 V DC-13 - electrical durability: 1000 cycles - for control circuit 180 W at 60 V DC-13 - electrical durability: 100000 cycles - for control circuit 24 W at 24 V DC-13 - electrical durability: 1000 cycles - for control circuit 240 W at 48 V DC-13 - electrical durability: 100000 cycles - for control circuit 9 W at 60 V DC-13 - electrical durability: 1000 cycles - for control circuit
------------------------------	--

---

Tightening torque	Control circuit: $\leq 1.4$ N.m - on screw-clamp terminals
-------------------	--

---

Height	89 mm
--------	-------

---

Width	9.3 mm
-------	--------

---

Depth	66 mm
-------	-------

---

Product weight	0.055 kg
----------------	----------

---

## Environment

---