



### Main

|                           |                    |
|---------------------------|--------------------|
| Product or component type | Switch             |
| Device short name         | KB32               |
| Device presentation       | Complete mechanism |

### Complementary

|                                |  |
|--------------------------------|--|
| Switch function                | 2-way  |
| Actuator                       | Rocker   |
| Number of gangs                | 2 gangs  |
| Colour tint                    | White  |
| Material                       | Polycarbonate (grid plate)<br>Polycarbonate (surround)<br>Polycarbonate (base) |
| Projecting depth               | 8 mm   |
| Device mounting                | Flush  |
| Mounting support               | Wall mounted   |
| Fixing mode                    | By screw M3.5  |
| Fixing center                  | 60.3 mm  |
| Embedding depth                | >= 35 mm   |
| Rated current                  | 16 AX at 250 V AC, inductive<br>16 AX at 250 V AC, fluorescent                 |
| [Ue] rated operational voltage | 250 V AC   |
| Network frequency              | 50 Hz  |
| Contacts material              | Brass and phosphor bronze  |
| Connections - terminals        | Pillar terminal  |
| Terminal identifier            | COM<br>L1<br>L2  |
| Tightening torque              | 0.4 N.m  |
| Clamping connection capacity   | 2.5 mm <sup>2</sup>  |
| Width                          | 87 mm  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|        |       |
|--------|-------|
| Height | 87 mm |
|--------|-------|

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | IEC 60669-1<br>SS 227<br>MS IEC 60669-1 |
| Ambient air temperature for operation | -5...40 °C                              |
| Relative humidity                     | 0...95 %                                |
| Environmental characteristic          | Indoor use                              |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0627 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|