



### Main

Range	TeSys
Product name	TeSys LC1D.K TeSys Deca
Product or component type	Capacitor duty contactor
Device short name	LC1DTK
Contactor application	Power factor correction
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit: ≤ 690 V AC 50/60 Hz
Reactive power rating	25 Kvar at 220...240 V AC 50/60 Hz 55 °C 40 Kvar at 400...440 V AC 50/60 Hz 55 °C 58 kvar at 660...690 V AC 50/60 Hz 55 °C
Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	220 V AC 50/60 Hz
Auxiliary contact composition	1 NO + 2 NC
Mounting support	Rail Plate
Standards	IEC 60070 NF C 54-100 VDE 0560 IEC 60831
Product certifications	UL CSA
Connections - terminals	Power circuit: connector 1 2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: connector 1 4 mm <sup>2</sup> - cable stiffness: solid with cable end Power circuit: connector 2 1.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: connector 2 4 mm <sup>2</sup> - cable stiffness: solid with cable end
Tightening torque	Power circuit: 5 N.m - on connector

### Complementary

Auxiliary contacts type	Type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 Type mirror contact 1 NC conforming to IEC 60947-4-1
-------------------------	--

### Environment

IP degree of protection	IP2x conforming to IEC 60529 IP2x conforming to VDE 0106
Protective treatment	TH conforming to IEC 60068-2-30
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	0...3000 m
Height	180 mm
Width	75 mm
Depth	150 mm
Net weight	1.3 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------