

# LC1E0910Q5



## LC1E0910Q5

Contactor irreversible EasyPact TVS LC1E, 9 A, 380V AC coil

### Main characteristics

Type	Contactor irreversible
Brand	EasyPact TVS LC1E
Application	Resistive load, motor control
Number of poles	3
3-phase power elektordvigatelya (AC-3 at Ue = 380 V), kW	4
Rated current (category AC-3), A	9
Rated voltage	690V
Tension Control	380V AC

### Characteristics of

## DESCRIPTION

Type	Contactor irreversible
Brand	EasyPact TVS LC1E
Application	Resistive load, motor control

## POWER CIRCUIT

Number of poles	3
3-phase power elektordvigatelya (AC-3 at Ue = 380 V), kW	4
Rated current (category AC-3), A	9
Rated voltage	690V
Mechanical life	10 million. Cycles
Electrical life (AC-3)	1.4 million. Cycles

## CONTROL CIRCUIT

Tension Control	380V AC
Consumption (when closed)	95 VA
Consumption (On Hold)	8,5 VA

Maximum operating rate

1800 cycles / hours, with  $t \leq 60^\circ \text{C}$

---

## ADDITIONAL CONTACTS

Extras. contact information

1NO

---

## TERMS OF USE

The ambient temperature during operation

$-5 \dots + 55^\circ \text{C}$

---

Temperature Ambient

$-60 \dots + 80^\circ \text{C}$

---

Ingress Protection

IP20

---

Dimensions (H / W / D), mm

74/45/80

---

Weight

0.3

---