

LC1E1210Q5



LC1E1210Q5

Contactor irreversible EasyPact TVS LC1E, 12 A, 380V AC coil

Main characteristics

Type	Contactor irreversible
Brand	EasyPact TVS LC1E
Application	Resistive load, motor control
Number of poles	3
3-phase power elektordvigatelya (AC-3 at Ue = 380 V), kW	5.5
Rated current (category AC-3), A	12
Rated voltage	690V
Tension Control	380V AC

Characteristics of

DESCRIPTION

Type	Contactor irreversible
Brand	EasyPact TVS LC1E
Application	Resistive load, motor control

POWER CIRCUIT

Number of poles	3
3-phase power elektordvigatelya (AC-3 at Ue = 380 V), kW	5.5
Rated current (category AC-3), A	12
Rated voltage	690V
Mechanical life	10 million. Cycles
Electrical life (AC-3)	1.4 million. Cycles

CONTROL CIRCUIT

Tension Control	380V AC
Consumption (when closed)	95 VA
Consumption (On Hold)	8,5 VA

Maximum operating rate

1800 cycles / hours, with $t \leq 60^\circ \text{C}$

ADDITIONAL CONTACTS

Extras. contact information

1NO

TERMS OF USE

The ambient temperature during operation

$-5 \dots + 55^\circ \text{C}$

Temperature Ambient

$-60 \dots + 80^\circ \text{C}$

Ingress Protection

IP20

Dimensions (H / W / D), mm

74/45/80

Weight

0.3
