

LC1E1810B5



LC1E1810B5

Contactir irreversible EasyPact TVS LC1E, 18 A, 24V AC coil

Main characteristics

Type	Contactir irreversible
Brand	EasyPact TVS LC1E
Application	Resistive load, motor control
Number of poles	3
3-phase power elektordvigatelya (AC-3 at Ue = 380 V), kW	7.5
Rated current (category AC-3), A	18
Rated voltage	690V
Tension Control	24V AC

Characteristics of

DESCRIPTION

Type	Contactir irreversible
Brand	EasyPact TVS LC1E
Application	Resistive load, motor control

POWER CIRCUIT

Number of poles	3
3-phase power elektordvigatelya (AC-3 at Ue = 380 V), kW	7.5
Rated current (category AC-3), A	18
Rated voltage	690V
Mechanical life	10 million. Cycles
Electrical life (AC-3)	1.2 million. Cycles

CONTROL CIRCUIT

Tension Control	24V AC
Consumption (when closed)	95 VA
Consumption (On Hold)	8,5 VA

Maximun operating rate 1800 cycles/ hours, with $t_{\leq 60} \leq 60$ C

ADDITIONAL CONTACTS

Extras contact information	1NO
----------------------------	-----

TERMS OF USE

The ambient temperature during operation	-5...+ 55 C
Temperature Ambient	-60...+ 80 C
Ingress Protection	IP20
Dimensions (H/W/D), mm	74/45/80
Weight	0.3