

LR9F5371

thermal overload relay for motor - TeSys LR9 -
132...220 A - class 10



Main

Range of product	TeSys F
Device short name	LR9F
Product or component type	Electronic thermal overload relay
Relay application	Motor
Product compatibility	LC1F185...LC1F400
Network type	DC
Overload tripping class	Class 10
Signalling function	Alarm
Thermal protection adjustment range	132...220 A
Protection type	AM fuses 250 A - for power circuit BS fuse 5 A - for control circuit GB2 circuit breaker 5 A - for control circuit GG fuse 315 A - for power circuit GG fuse 5 A - for control circuit
Quantity per set	Set of 10

Complementary

Network frequency	50/60 Hz
[Us] rated supply voltage	24 V DC
Supply voltage limits	17...32 V
Mounting support	Direct on contactor Rail
Tripping threshold	1.05 +/- 0.06 In alarm conforming to IEC 60947-4-1 1.12 +/- 0.06 In tripping conforming to IEC 60947-4-1
Surge withstand	4 kV conforming to IEC 61000-4-5
[Ith] conventional free air thermal current	5 A for control circuit
Maximum power	100 VA at 24 V AC 100 W at 24 V DC 100 W at 48 V DC 200 VA at 48 V AC 25 W at 440 V DC 400 VA at 110 V AC 45 W at 220 V DC 50 W at 110 V DC 600 VA at 220 V AC 600 VA at 380 V AC 600 VA at 600 V AC
[Ue] rated operational voltage	1000 V AC 50/60 Hz for power circuit conforming to VDE 0110 group C
[Ui] rated insulation voltage	1000 V AC power circuit conforming to IEC 60947-4
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-1
Phase failure sensitivity	Tripping in 4 s +/- 20 % conforming to IEC 60947-4-1
Reset	Manual reset on front relay
Temperature compensation	-20...70 °C
Current consumption	<= 5 mA no-load
Switching capacity in mA	0...150 mA
Output overload protection	Auto-protected
Output short-circuit protection	Auto-protected
Voltage drop	<= 2.5 V closed state
Connections - terminals	Control circuit: screw clamp terminals 2 cable 1 mm ² - cable stiffness: solid Power circuit: lugs Control circuit: screw clamp terminals 2 cable 1...2.5 mm ² - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 1 cable 0.75...4 mm ² - cable stiffness: flexible -

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

without cable end

Control circuit: screw clamp terminals 1 cable 0.75...2.5 mm² - cable stiffness: flexible - with cable end

Control circuit: screw clamp terminals 1 cable 0.75...2.5 mm² - cable stiffness: solid
Control circuit: screw clamp terminals 2 cable 1...1.5 mm² - cable stiffness: flexible - with cable end

Tightening torque	Power circuit: 35 N.m - on screw clamp terminals Control circuit: 1.2 N.m - on screw clamp terminals Alarm circuit: 0.45 N.m
Height	101 mm
Width	120 mm
Depth	123.5 mm
Product weight	0.95 kg

Environment

Standards	EN 60947-4-1 IEC 60255-17 IEC 60255-8 IEC 60947-4-1 VDE 0660
Product certifications	CSA GOST UL
Protective treatment	TH standard version
IP degree of protection	IP20 conforming to IEC 60529 IP20 conforming to VDE 0106
Ambient air temperature for operation	-20...55 °C conforming to IEC 60255-8
Ambient air temperature for storage	-40...85 °C
Operating altitude	<= 2000 m without derating
Fire resistance	850 °C conforming to IEC 60695-2-1
Shock resistance	13 gn 11 ms conforming to IEC 60068-2-7
Vibration resistance	2 gn 5...300 Hz conforming to IEC 60068-2-6
Dielectric strength	6 kV at 50 Hz conforming to IEC 255-5
Resistance to electrostatic discharge	6 kV in indirect mode conforming to IEC 61000-4-2 8 kV in air conforming to IEC 61000-4-2
Resistance to radiated fields	10 V/m conforming to IEC 61000-4-3
Resistance to fast transients	2 kV conforming to IEC 61000-4-4