



Main

Range of product	TeSys D
Device short name	LRD
Product or component type	Differential thermal overload relay
Relay application	Motor protection
Product compatibility	LC1D150
Network type	AC
Overload tripping class	Class 10A IEC 60947-4-1
Thermal protection adjustment range	110...140 A
Protection type	BS88 fuse 200 A power circuit BS fuse 5 A control circuit GB2 circuit breaker 5 A control circuit AM fuses 160 A power circuit GG fuse 250 A power circuit GG fuse 5 A control circuit
Connections - terminals	Screw clamp terminals power circuit 1 4...50 mm ² solid without Screw clamp terminals power circuit 1 4...35 mm ² flexible with Screw clamp terminals control circuit 1 1...2,5 mm ² flexible without Screw clamp terminals control circuit 2 1...2,5 mm ² flexible without Screw clamp terminals control circuit 1 1...2,5 mm ² flexible with Screw clamp terminals control circuit 2 1...2,5 mm ² flexible with Screw clamp terminals power circuit 1 4...50 mm ² flexible without Screw clamp terminals control circuit 2 1...2,5 mm ² solid without Screw clamp terminals control circuit 1 1...2,5 mm ² solid without
Quantity per set	Set of 10

Complementary

Network frequency	≤ 400 Hz
Mounting support	Under contactor
Tripping threshold	1.14 +/- 0.06 I _r IEC 60947-4-1
Surge withstand	6 kV IEC 60801-5
[I _{th}] conventional free air thermal current	5 A control circuit
[U _e] rated operational voltage	1000 V AC 50/60 Hz power circuit IEC 60947-4-1
[U _i] rated insulation voltage	1000 V power circuit IEC 60947-4-1
[U _{imp}] rated impulse withstand voltage	6 kV
Phase failure sensitivity	Tripping current I 30 % of I _r on one phase, the others at I _r IEC 60947-4-1
Reset	Automatic reset Manual reset
Temperature compensation	-20...60 °C
Tightening torque	1,7 N.m control circuit screw clamp terminals 9 N.m power circuit screw clamp terminals
Height	132 mm
Width	95 mm
Product weight	0,9 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	CSA C22-2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Product certifications	BV CCC CSA GOST RINA UL
Protective treatment	TH IEC 60068
IP degree of protection	IP2x VDE 0106
Ambient air temperature for operation	-40...70 °C with derating IEC 60947-4-1 -20...60 °C without derating IEC 60947-4-1
Ambient air temperature for storage	-60...70 °C
Fire resistance	850 °C IEC 60695-2-1
Shock resistance	15 gn 11 ms IEC 60068-2-7
Vibration resistance	6 gn on plate IEC 60068-2-6
Dielectric strength	6 kV 50 Hz IEC 60255-5
RoHS EUR conformity date	0849
RoHS EUR status	Compliant