



### Main

Range of product	TeSys F
Product or component type	Contactor coil
Product compatibility	LC1F265 LC1F330
Control circuit type	AC
Coil type	Low consumption
[Uc] control circuit voltage	110...115 V AC 50/60 Hz

### Complementary

Auxiliary contact composition	1 NO
Average resistance	440 Ohm at 20 °C sealed 18.7 Ohm at 20 °C inrush
Inrush power in VA	600...700 VA at 20 °C (cos φ 0.9)
Hold-in power consumption in VA	8...10 VA at 20 °C (cos φ 0.9) 50/60 Hz
Operating time	100...170 ms opening 40...65 ms closing
Mechanical durability	10000000 cycles
Operating rate	2400 cyc/h at ≤ 55 °C
Connections - terminals	Connector control circuit: 1 cable 1...4 mm <sup>2</sup> - cable stiffness: flexible - with cable end Connector control circuit: 1 cable 1...4 mm <sup>2</sup> - cable stiffness: flexible - without cable end Connector control circuit: 1 cable 1...4 mm <sup>2</sup> - cable stiffness: solid - without cable end Connector control circuit: 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Connector control circuit: 2 cable 1...4 mm <sup>2</sup> - cable stiffness: flexible - without cable end
Tightening torque	1.2 N.m control circuit: - on connector
Product weight	0.75 kg

### Environment

Heat dissipation	8 W at 50/60 Hz for control circuit
------------------	-------------------------------------