

# เอกสารข้อมูลผลิตภัณฑ์

## ลักษณะ

# M3T31\_1F\_GY

Switch, Avataron A , 16AX 250V, 1 Way with  
Fluorescent S sized, Grey



## Main

Range of product	AvatarOn A
Product or component type	Switch
Load type	Resistive load Inductive Fluorescent load
Colour tint	Grey

## Complementary

Device presentation	Complete product
Rated current	16 AX at 250 V AC 50 Hz
Switch function	1-way
Switch application	Control switch
Clamping connection capacity	2 x 1.5 mm <sup>2</sup> for solid cable(s) 2 x 2.5 mm <sup>2</sup> for stranded cable(s) 2 x 4 mm <sup>2</sup>
Connections - terminals	Screwless type terminals
Local signalling	Fluorescent (grey)
Material	PC: dolly PC 10 % GF: base PC 10 % GF: base cover
Device mounting	Flush
Width	23.1 mm
Height	69.3 mm
Depth	33 mm
Embedding depth	22 mm

## Environment

IP degree of protection	IP20
-------------------------	------

Maximum ambient air temperature for operation	45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
Operating altitude	<= 2000 m
Standards	IEC 60669-1
Product certifications	IEC TIS SNI

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>