



Main

Range of product	AvatarOn A
Product or component type	Switch
Load type	Resistive load Inductive Fluorescent load
Colour tint	White (WE)

Complementary

Device presentation	Complete product
Rated current	16 AX at 250 V AC 50 Hz
Switch function	2-way
Switch application	Control switch
Clamping connection capacity	2 x 1.5 mm ² for solid cable(s) 2 x 2.5 mm ² for stranded cable(s) 2 x 4 mm ²
Connections - terminals	Screwless type terminals
Local signalling	Fluorescent (white)
Material	PC: dolly PC 10 % GF: base PC 10 % GF: base cover
Device mounting	Flush
Width	34.85 mm
Height	69.3 mm
Depth	32.7 mm
Embedding depth	21.7 mm

Environment

IP degree of protection	IP20
-------------------------	------

Maximum ambient air temperature for operation	45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
Operating altitude	<= 2000 m
Standards	IEC 60669-1
Product certifications	IEC TIS

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information