



## Main

Range of product	AvatarOn A
Product or component type	Switched socket
Device application	Power supply
Device presentation	Complete product
Colour tint	Black

## Complementary

Range compatibility	AvatarOn
Rated current	16 A socket-outlet
[Ue] rated operational voltage	250 V AC 50...60 Hz
Socket number	2
Outlet standard description	3 pins
Outlet standard	Universal
Switch function	1-way
Number of gangs	2 gangs
Connections - terminals	Push-in
Number of terminals	3
Clamping connection capacity	2 x 1.5...2 x 4 mm <sup>2</sup> for solid cable(s) 2 x 1.5...2 x 4 mm <sup>2</sup> for stranded cable(s)
Wire stripping length	13 mm
Material	Polycarbonate: cover Polycarbonate: base Polycarbonate: dolly
Surface finish	Glossy Glossy and matt Glossy
Device mounting	Flush
Fixing mode	By 2 screws

Height	70 mm
Width	120 mm
Depth	30.3 mm
Embedding depth	19.3 mm
Net weight	0.118 kg

## Environment

IP degree of protection	IP20
Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
Standards	IEC 60884-2-3

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>