



## Main

Range of product	AvatarOn A
Product or component type	Switched socket
Device application	Power supply
Device presentation	Complete product
Colour tint	White

## Complementary

Range compatibility	AvatarOn
Rated current	16 A socket-outlet
[Ue] rated operational voltage	250 V AC 50...60 Hz
Socket number	2
Outlet standard description	3 pins
Outlet standard	Universal
Switch function	1-way
Number of gangs	2 gangs
Connections - terminals	Push-in
Number of terminals	3
Clamping connection capacity	2 x 1.5...2 x 4 mm <sup>2</sup> for solid cable(s) 2 x 1.5...2 x 4 mm <sup>2</sup> for stranded cable(s)
Wire stripping length	13 mm
Material	Polycarbonate: cover Polycarbonate: base Polycarbonate: dolly
Surface finish	Glossy Glossy and matt Glossy
Device mounting	Flush
Fixing mode	By 2 screws

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	70 mm
Width	120 mm
Depth	30.3 mm
Embedding depth	19.3 mm
Net weight	0.118 kg

## Environment

IP degree of protection	IP20
Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
Standards	IEC 60884-2-3

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>