



Main

Range of product	AvatarOn A
Product or component type	USB charger
Mounting mode	Flush-mounted
Integrated connection type	1 USB port 5 V AC/DC, maximum load current: 2.1 A

Complementary

Device presentation	Complete product
Colour tint	Grey
Surface finish	Matt
Surface treatment	Painted
Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
[Ue] rated operational voltage	110...220 V 50...60 Hz
Input power	10.5 W
Maximum load current with 2 outputs used simultaneously	2.1 A
Material	PC (UL94 V-0)
Clamping connection capacity	0.5...4 mm ² for solid or flexible cable(s)
Height	69.3 mm
Width	23.1 mm
Depth	35.5 mm
Embedding depth	24.5 mm

Environment

Standards	IEC 62368-1
-----------	-------------

Product certifications	IEC
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile