



Main

Range of product	AvatarOn A
Product or component type	Switch
Load type	Resistive load Inductive Capacitive
Colour tint	Black (BK)

Complementary

Device presentation	Complete product
Rated current	3 A at 24 V DC
Switch function	2-way
Switch application	Panic button
Number of gangs	1 gang
Clamping connection capacity	2 x 1 mm ² for solid cable(s) 2 x 1.5 mm ² for stranded cable(s) 1 x 2.5 mm ²
Connections - terminals	Terminal block
Material	PC: grid plate PC: cover PC: button
Device mounting	Flush
Width	120 mm
Height	70 mm
Depth	34.2 mm
Embedding depth	23.2 mm

Environment

IP degree of protection	IP20
-------------------------	------

Maximum ambient air temperature for operation	45 °C
Ambient air temperature for storage	-5...60 °C
Relative humidity	0...95 %
Operating altitude	<= 2000 m
Standards	IEC 60670-1
Product certifications	IEC

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information