

RXM4AB2BD

miniature plug-in relay - Zelio RXM - 4 C/O - 24 V DC - 6 A - with LED



Main

Range of product	Zelio Relay
Series name	Miniature
Product or component type	Plug-in relay
Device short name	RXM
Status LED	With
Control type	Pushbutton
Control circuit voltage	24 V DC
Contacts type and composition	4 C/O
Contacts operation	Standard
Coil interference suppression	Without
[Ithe] conventional enclosed thermal current	6 A ≤ 55 °C
Contacts material	Silver alloy (Ag/Ni)
Load current	6 A 250 V AC 6 A 28 V DC
Utilisation coefficient	20 %
Rated operational voltage limits	19.2...26.4 V DC
Sale per indivisible quantity	10

Complementary

[Ui] rated insulation voltage	250 V IEC 300 V UL 300 V CSA
[Uimp] rated impulse withstand voltage	4 kV IEC 61000-4-5
[Ie] rated operational current	3 A NC AC-1/DC-1 IEC 6 A NO AC-1/DC-1 IEC 8 A AC-1/DC-1 UL
Minimum switching current	10 mA
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	17 V
Maximum switching capacity	168 W DC 1500 VA AC
Minimum switching capacity	170 mW
Operating rate	≤ 20 cyc/mn under load ≤ 300 cyc/mn no-load
Mechanical durability	10000000 cycles
Electrical durability	100000 cycles resistive
Average consumption in W	0,9 W DC
Average consumption in VA	1,2 AC
Drop-out voltage threshold	>= 0.15 Uc AC >= 0.1 Uc DC
Operating time	20 ms between coil de-energisation and making of the Off-delay contact AC/DC 20 ms between coil energisation and making of the On-delay contact AC/DC
Average resistance	650 Ohm DC 20 °C +/- 10 %
Protection category	RT I
Operating position	Any position
Product weight	0,037 kg

Environment

Dielectric strength	1500 V AC between contacts 1550 V AC between coil and contact 1550 V AC between poles
Product certifications	CSA UL
Standards	CSA C22-2 No 14 EN/IEC 61810-1 (iss. 2) UL 508
Ambient air temperature for storage	-40...85 °C
Ambient air temperature for operation	-40...55 °C
Vibration resistance	3 gn +/- 1 mm 10...150 Hz opening EN/IEC 60068-2-27 5 gn +/- 1 mm 10...150 Hz closing EN/IEC 60068-2-27
IP degree of protection	IP40 EN/IEC 60529
Shock resistance	15 gn closing EN/IEC 60068-2-27 15 gn opening EN/IEC 60068-2-27
RoHS EUR conformity date	0801
RoHS EUR status	Compliant