

RXZE2M114

socket RXZ - mixed contact -10A - < 250V -
screw clamp -for relay RXM2..., RXM4..



Main

Range of product	Zelio Relay
Product or component type	Socket
Contact terminal arrangement	Mixed
Product compatibility	Relay RXM2.... Relay RXM4....
Device short name	RXZ
[I _{th}] conventional free air thermal current	10 A
Connections - terminals	Screw clamp terminals 2 x 0.5...2 x 1.5 mm ² AWG20...AWG16 solid without cable end Screw clamp terminals 2 x 0.25...2 x 1 mm ² AWG22...AWG17 flexible with cable end Screw clamp terminals 1 x 0.25...1 x 1 mm ² AWG22...AWG17 flexible with cable end Screw clamp terminals 1 x 0.5...1 x 1.5 mm ² AWG20...AWG16 solid without cable end
Sale per indivisible quantity	10

Complementary

[U _e] rated operational voltage	< 250 V
Tightening torque	≤ 1 N.m M3
Fixing mode	By screw panel Clip-on 35 mm symmetrical DIN rail
Marking	CE
Width	30 mm
Product weight	0,048 kg

Environment

Standards	IEC 61984
Product certifications	CSA UL
Ambient air temperature for storage	-40...85 °C
Ambient air temperature for operation	-40...55 °C
IP degree of protection	IP20 EN/IEC 60529
Dielectric strength	2500 V
RoHS EUR conformity date	0801
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.