



Main

Range	TeSys
Device short name	VZ
Product or component type	Additional earthing block
Performance level	High performance
Product compatibility	V02 V1 V2 V0 V01
Network type	AC DC
Network frequency	50/60 Hz
Mounting location	Left Right

Complementary

[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ith] conventional free air thermal current	40 A
Mechanical durability	100000 cycles
Electrical durability	100000 cycles AC-15 30000 cycles DC-11
Connections - terminals	Screw clamp terminals
Height	74 mm
Width	16 mm
Depth	35 mm
Product weight	0.05 kg

Environment

Standards	IEC 60947-3
Product certifications	CSA GL UL
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Shocks 11 ms 15 gn IEC 60068-2-27 Vibrations 10...150 Hz 5 gn IEC 60068-2-6
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.