

Control and signaling units Ø 22

Harmony Easy XA2, plastic
Pushbuttons, switches and pilot lights: complete units

Functions (continued)

Contact functions (continued)

Selector or key switches, 2 or 3-position



Type of push	Standard handle	Long handle	Key
Degree of protection	IP 54	IP 54	IP 54
Reference	XA2ED ••	XA2EJ ••	XA2EG21/EG •3
Pages	11		

Combined functions: contact and signaling

Illuminated pushbuttons, spring return



Type of push	Flush push
Degree of protection	IP 54
LED	Integral LEDs, 24, 220-230 or 380-400 V
Color	White, Green, Red, Yellow, and Blue
Reference	XA2EW3 •B1/3•M1/3•Q1
Pages	12

Signaling functions

Pilot lights



Degree of protection	IP 40
LED	Integral LEDs, 24, 110, 220-230 or 380-400 V
Color	White, Green, Red, Yellow, and Blue
Reference	XB7EV •LC/EV•De/LC
Pages	13

References:
page 9

8



References

Control and signaling units Ø 22

Harmony Easy XA2, plastic
Spring return pushbuttons, marked and unmarked
Mushroom head pushbuttons, spring return



Spring return pushbuttons with flush push

Shape of head	Type of contacts	Color of push	Marking	Reference	Weight kg/lb
Unmarked		White	–	XA2EA11	0.032/0.071
		Black	–	XA2EA21	0.032/0.071
		Green	–	XA2EA31	0.032/0.071
		Yellow	–	XA2EA51	0.032/0.071
		Blue	–	XA2EA61	0.032/0.071
		Red	–	XA2EA42	0.032/0.071
Marked		Green	"I"	XA2EA3311	0.032/0.071
		Black	"↑"	XA2EA3351	0.032/0.071
		White	"↑"	XA2EA3341	0.032/0.071
		Red	"O"	XA2EA4322	0.032/0.071
		Red	"STOP"	XA2EA4342	0.032/0.071

Mushroom head pushbuttons, spring return

Shape of head	Type of contacts	Color of push	Diameter Ø (mm)/in.	Reference	Weight kg/lb
		Black	40/1.575	XA2EC21	0.052/0.115
		Green	40/1.575	XA2EC31	0.052/0.115
		Red	40/1.575	XA2EC42	0.052/0.115
		Yellow	40/1.575	XA2EC51	0.052/0.115
		Black	60/2.362	XA2ER21	0.058/0.128

Note: Please refer to our website www.schneider-electric.com for information on dimensions

General:
page 6



9