

Control and signaling units Ø 22

Harmony Easy XA2, plastic

Illuminated pushbuttons with flush push

Bulbs for illuminated pushbuttons

Contact functions for all XA2 pushbuttons and switches



XA2EW36B1



DL1LED244



DL1LED246



ZB5AZ905



ZB5AZ902



ZA2EE102

Illuminated pushbuttons with integral LED

Shape of head	Type of push	Supply voltage V	Type of contacts		Color	Reference	Weight kg/lb
			N/O	N/C			
Ø 22	Flush push	~ / ≍ 24	1	-	White	XA2EW31B1	0.056/0.123
					Green	XA2EW33B1	0.056/0.123
					Red	XA2EW34B1	0.056/0.123
					Yellow	XA2EW35B1	0.056/0.123
					Blue	XA2EW36B1	0.056/0.123
					Red	XA2EW34B2	0.056/0.123
	~ 220-230	1	-	White	XA2EW31M1	0.064/0.141	
				Green	XA2EW33M1	0.064/0.141	
				Red	XA2EW34M1	0.064/0.141	
				Yellow	XA2EW35M1	0.064/0.141	
				Blue	XA2EW36M1	0.064/0.141	
				Red	XA2EW34M2	0.056/0.123	
~ 380-400	1	-	White	XA2EW31Q1	0.064/0.141		
			Green	XA2EW33Q1	0.064/0.141		
			Red	XA2EW34Q1	0.064/0.141		
			Yellow	XA2EW35Q1	0.064/0.141		
			Blue	XA2EW36Q1	0.064/0.141		
			Red	XA2EW34Q2	0.056/0.123		

Bulbs with BA 9s base fitting and associated accessories

Description	Characteristics	Color	Sold in lots of	Unit reference	Weight kg/lb
LEDs	~ / ≍ 24 V	White	10	DL1LED241	0.002/0.004
		Green	10	DL1LED243	0.002/0.004
		Red	10	DL1LED244	0.002/0.004
		Yellow	10	DL1LED245	0.002/0.004
		Blue	10	DL1LED246	0.002/0.004

Description	Application	Sold in lots of	Unit reference	Weight kg/lb
Bezel tool	Tightening head fixing nut	1	ZB5AZ905	0.016/0.035
Anti-rotation plate	Prevents head from rotation	10	ZB5AZ902	0.008/0.018

Contact functions (for all XA2 pushbuttons and switches)

Screw clamp terminal connections

Description	To be used with	Type of contacts		Sold in lots of	Unit reference	Weight kg/lb
		N/O	N/C			
Contact blocks	All XA2 pushbuttons and switches	1	-	1	ZA2EE101	0.014/0.031
		-	1	1	ZA2EE102	0.014/0.031

Note: Please refer to our website www.schneider-electric.com for information on dimensions

Control and signaling units Ø 22

Harmony Easy XA2, plastic
Pilot lights with integral LED

Pilot lights with integral LED

Shape of head	Supply voltage V	Color of lens	Sold in lots of	Reference	Weight kg/lb
●	~ / ≍ 24	White	10	XA2EVB1LC	0.017/0.037
		Green	10	XA2EVB3LC	0.017/0.037
		Red	10	XA2EVB4LC	0.017/0.037
		Yellow	10	XA2EVB5LC	0.017/0.037
		Blue	10	XA2EVB6LC	0.017/0.037
		~ 110	~ 110	White	10
Green	10			XA2EVF3LC	0.017/0.037
Red	10			XA2EVF4LC	0.017/0.037
Yellow	10			XA2EVF5LC	0.017/0.037
Blue	10			XA2EVF6LC	0.017/0.037
≍ 110	≍ 110			White	10
		Green	10	XA2EVFD3LC	0.017/0.037
		Red	10	XA2EVFD4LC	0.017/0.037
		Yellow	10	XA2EVFD5LC	0.017/0.037
		Blue	10	XA2EVFD6LC	0.017/0.037
		~ 220-230	~ 220-230	White	10
Green	10			XA2EVM3LC	0.017/0.037
Red	10			XA2EVM4LC	0.017/0.037
Yellow	10			XA2EVM5LC	0.017/0.037
Blue	10			XA2EVM6LC	0.017/0.037
≍ 220	≍ 220			White	10
		Green	10	XA2EVMD3LC	0.017/0.037
		Red	10	XA2EVMD4LC	0.017/0.037
		Yellow	10	XA2EVMD5LC	0.017/0.037
		Blue	10	XA2EVMD6LC	0.017/0.037
		~ 380-400	~ 380-400	White	10
Green	10			XA2EVQ3LC	0.017/0.037
Red	10			XA2EVQ4LC	0.017/0.037
Yellow	10			XA2EVQ5LC	0.017/0.037
Blue	10			XA2EVQ6LC	0.017/0.037

Note: Please refer to our website www.schneider-electric.com for information on dimensions

D			
DL1LED241	12	XA2EVFD5LC	13
DL1LED243	12	XA2EVFD6LC	13
DL1LED244	12	XA2EVM1LC	13
DL1LED245	12	XA2EVM3LC	13
DL1LED246	12	XA2EVM4LC	13
		XA2EVM5LC	13
		XA2EVM6LC	13
X			
XA2EA11	9	XA2EVMD1LC	13
XA2EA21	9	XA2EVMD3LC	13
XA2EA31	9	XA2EVMD4LC	13
XA2EA42	9	XA2EVMD5LC	13
XA2EA51	9	XA2EVMD6LC	13
XA2EA61	9	XA2EVQ1LC	13
XA2EA3311	9	XA2EVQ3LC	13
XA2EA3341	9	XA2EVQ4LC	13
XA2EA3351	9	XA2EVQ5LC	13
XA2EA4322	9	XA2EVQ6LC	13
XA2EA4342	9	XA2EW31B1	12
XA2EC21	9	XA2EW31M1	12
XA2EC31	9	XA2EW31Q1	12
XA2EC42	9	XA2EW33B1	12
XA2EC51	9	XA2EW33M1	12
XA2ED21	11	XA2EW33Q1	12
XA2ED25	11	XA2EW34B1	12
XA2ED33	11	XA2EW34B2	12
XA2ED41	11	XA2EW34M1	12
XA2ED53	11	XA2EW34M2	12
XA2EG03	11	XA2EW34Q1	12
XA2EG21	11	XA2EW34Q2	12
XA2EG33	11	XA2EW35B1	12
XA2EG43	11	XA2EW35M1	12
XA2EG63	11	XA2EW35Q1	12
XA2EG73	11	XA2EW36B1	12
XA2EH011	10	XA2EW36M1	12
XA2EH021	10	XA2EW36Q1	12
XA2EH031	10		
		Z	
XA2EH042	10	ZA2EE101	12
XA2EH051	10	ZA2EE102	12
XA2EH061	10	ZB5AZ902	12
XA2EJ21	11	ZB5AZ905	12
XA2EJ25	11		
XA2EJ33	11		
XA2EJ53	11		
XA2ER21	9		
XA2ES422	10		
XA2ES442	10		
XA2ES542	10		
XA2ES642	10		
XA2ET42	10		
XA2EVB1LC	13		
XA2EVB3LC	13		
XA2EVB4LC	13		
XA2EVB5LC	13		
XA2EVB6LC	13		
XA2EVF1LC	13		
XA2EVF3LC	13		
XA2EVF4LC	13		
XA2EVF5LC	13		
XA2EVF6LC	13		
XA2EVFD1LC	13		
XA2EVFD3LC	13		
XA2EVFD4LC	13		

Schneider Electric Industries SAS

Head Office
35, rue Joseph Monier
F-92500 Rueil-Malmaison
France

www.schneider-electric.com

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Design: Schneider Electric
Photos: Schneider Electric

DIA5ED2140104EN