



Main

Range of product	Zelio Count
Product or component type	Hour counter
Display type	Mechanical
Size	48 x 48 mm
Display digits	7 digit(s)
Reset	Without
Technology type	Electromechanical

Complementary

[Us] rated supply voltage	230 V AC (Us +/- 10 %)
Power consumption	1 VA
Backup time	Permanent
Counting mode	Adding 1/100 of an hour
Time range	0...99 999,99 h
Input function	Enable
Input type	Contact
Mounting mode	Flush-mounted
Mounting support	Panel mounting
Fixing mode	By self-locking clamp
Connections - terminals	Screw terminal block
Height	48 mm
Product weight	0.06 kg
Width	48 mm
Character size	5 mm
CAD overall width	48 mm
CAD overall height	48 mm
CAD overall depth	63 mm

Environment

Standards	VDE 0435 EN/IEC 50082-2 EN/IEC 50081-2
Product certifications	UR
IP degree of protection	IP65 conforming to EN/IEC 60529
Ambient air temperature for operation	-10,0 °C...50,0 °C
Ambient air temperature for storage	-25,0 °C...70,0 °C
Vibration resistance	3 gn (f = 10...150 Hz) conforming to EN/IEC 60068-2-6
Shock resistance	30 gn for 11 ms conforming to EN/IEC 60068-2-27
Class of protection against electric shock	Class II conforming to EN/IEC 60536


The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Electromechanical and Electronic Totalizing Timers

Timers with Mechanical Display


XBKH7000000•M

mm
in.



Flush-Mounting


mm
in.



Timers with LCD Display

XBKH81000033E

mm
in.



Flush-Mounting

mm
in.

