



## XVGB4S

Tower Light - RAGB - 24V - LED Based - W. Buzzer - Tube mounting with L bracket



### Main

Range of product	Harmony XVG
Product or component type	Complete pre-wired monolithic tower light
Beacon or indicator bank unit type	4 illuminated units
Material	PC (UL94 V-2) globe ABS (UL94HB) tube body Aluminium tube
Mounting diameter	60 mm
Component name	XVG
Device mounting	Tube with L bracket
Light source	LED steady blue LED steady green LED steady red LED steady amber
Light block color	Red/amber/green/blue
Indicator bank base type	Base with integrated buzzer

### Complementary

[Us] rated supply voltage	24 V AC/DC
Cable cross section	0.33 mm <sup>2</sup>
[Uimp] rated impulse withstand voltage	0.5 kV
Current consumption	207 mA
Noise level	85 dB
Power consumption	4.8 W
Fundamental frequency	2.64 kHz
Product weight	0.51 kg

### Environment

Product certifications	CE
Ambient air temperature for storage	-35...70 °C
Ambient air temperature for operation	-10...50 °C
IP degree of protection	IP23

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1140 - Schneider Electric declaration of conformity